





M26L - HALOSCAN MP SOFT 93014 DIM5

23126 9015 W

AVAILABLE IN
BLACK 23126 9015 B
WHITE 23126 9015 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 45° swiveling, 355° rotatable
INFORMATION	LENS SP-14° EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM2
RISKGROUPE	RG1
LM80	L90B10 > 50000
BEAMANGLE	14°
LED TECHNICS (LIGHT SOURCE)	623lm // 6W // 105lm/W
LED TECHNICS (LUMINAIRE)	532lm // 6,9W // 77lm/W

Remarks

[Take a look at our MAGNETIC PROFILES movie](#)

Requirements

LED POWER SUPPLY 48V-DC

Accessories


HALOSCAN HONEYCOMB
 HALOSCAN LINEAR SPREAD LENS
 HALOSCAN KAP MP

For detailed installation instructions, please consult the manual : **23126_XXX5_HAND.pdf**

DELTALIGHT

M26L - HALOSCAN MP SOFT 93014 DIM5

23126 9015 W



23110 0060 B HALOSCAN KAP MP B




23110 0060 W HALOSCAN KAP MP W




COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)


Available Colours




23358 0000 SLM26L - PROFILE



23358 0010 SLM26L - PROFILE 1m



23358 0020 SLM26L - PROFILE 2m




23358 0030 SLM26L - PROFILE 3m




SHIFTLINE M35R profile


Available Colours



23375 0000 SLM35R - PROFILE



23375 0010 SLM35R - PROFILE 1m




23375 0020 SLM35R - PROFILE 2m



M26L - HALOSCAN MP SOFT 93014 DIM5

23126 9015 W



23375 0030 SLM35R - PROFILE 3m



Notes: