

ENTERO RD-L TRIMLESS 92730



28435 9220 B

AVAILABLE IN

BLACK 28435 9220 B

FULL WHITE 28435 9220 FW

GOLD COLOURED 28435 9220 GC



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - Ø KIT
RECESSED DEPTH (MM)	165
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.67
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-30° EXCL.LED POWER SUPPLY 350-1050mA-DC Optional REFLECTORS 18° & 45° available

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,3-36,5W / CRI>90 (R9: 60) / 2700K / 1561-4380lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	4380lm // 36,5W // 120lm/W
LED TECHNICS (LUMINAIRE)	3479lm // 42W // 83lm/W

Remarks

Max.900mA when using 1 accessory; max 800mA when using 2 accessories

Requirements

MOUNTING KIT ENTERO ROUND L

LED POWER SUPPLY 350 / 500 / 700 / 1050mA-DC DIM (Remote)

Accessories

- ENTERO L HONEYCOMB
- ENTERO L LINEAR SPREAD LENS
- ENTERO L SPREAD LENS
- ENTERO L SOFTENING LENS
- ENTERO L GLASS SBL
















DELTALIGHT

ENTERO RD-L TRIMLESS 92730




28435 9220 B

For detailed installation instructions, please consult the manual : [28435_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 System ceiling	 28400 0030 - MOUNTING KIT ENTERO RD-L	Required
 Plasterboard	 28400 0030 - MOUNTING KIT ENTERO RD-L	Required
 Stucanet	 28400 0030 - MOUNTING KIT ENTERO RD-L	Required
 Concrete + plaster	 28400 0030 - MOUNTING KIT ENTERO RD-L	Required
 Lintel + plaster	 28400 0030 - MOUNTING KIT ENTERO RD-L	Required
 Hollow-core slab + plaster	 28400 0030 - MOUNTING KIT ENTERO RD-L	Required
 Stretched ceiling	 28400 0090 - MOUNTING KIT ENTERO RD-L CSC	Required
	 28400 0150 - MOUNTING KIT ENTERO RD-L WSC	Required


FINISH YOUR SPECIFICATION

LED power supplies	# of Fixtures
<p> # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.</p>	
<p> 300 90 63 LED POWER SUPPLY MULTI-POWER DIM9</p> <p>Dimtype: 1-10V or DALI or push button</p> <p>Cutout dimension (mm): 82</p>	<p>Min current Max current</p> <p>2(2) 2(2) 2(1) - <input type="checkbox"/></p>
<p> 300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9</p> <p>Dimtype: 1-10V or DALI or push button</p>	<p>1 <input type="checkbox"/></p>

DELTALIGHT

ENTERO RD-L TRIMLESS 92730

28435 9220 B




300 90 135 LED POWER SUPPLY MULTI-POWER HV

1

Dimtype: non-dimmable

Cutout dimension (mm): 90




300 90 136 LED POWER SUPPLY MULTI-POWER HC DIM9

1(1)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 90




21012 0010 LED POWER SUPPLY MULTI POWER

1

Dimtype: non-dimmable

Cutout dimension (mm): 50




21012 0021 LED POWER SUPPLY MULTI POWER DIM1

1

Dimtype: 1-10V

Cutout dimension (mm): 54




21012 0035 LED POWER SUPPLY MULTI POWER DIM5

1

Dimtype: DALI

Cutout dimension (mm): 54




21012 004W LED POWER SUPPLY MULTI-POWER WDL

1(1)

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 84




21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL

1

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 54




21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68

1(1)

Dimtype: non-dimmable

Cutout dimension (mm): 60




21012 0490 LED POWER SUPPLY 700mA-DC / 30W IP68

1(0)

Dimtype: non-dimmable

Cutout dimension (mm): 60



21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68

1(0)

Dimtype: non-dimmable


Cutout dimension (mm): 60

DELTALIGHT

ENTERO RD-L TRIMLESS 92730

28435 9220 B


Mounting kits



28400 0030 MOUNTING KIT ENTERO RD-L

Cutout dimension (mm): 162

Mounting kits stretched ceiling



28400 0090 MOUNTING KIT ENTERO RD-L CSC




28400 0150 MOUNTING KIT ENTERO RD-L WSC


Light altering devices




28500 0130 ENTERO L LINEAR SPREAD LENS




28500 0140 ENTERO L SPREAD LENS



28500 0150 ENTERO L SOFTENING LENS



28500 0160 ENTERO L GLASS SBL




28500 0170 B ENTERO L HONEYCOMB SINGLE USE B

DELTALIGHT

ENTERO RD-L TRIMLESS 92730

28435 9220 B



28500 0180 B ENTERO L HONEYCOMB DOUBLE USE B



Notes: