MONO



Mono is a well-known member of the Delta Light outdoor range. It's been available in LED for a while and now has additional enhancements. Mono is the first outdoor wall fixture to combine the Delta Light LED array with a lens, resulting in a far-reaching and strongly delineated lighting effect. The Mono's timeless and sharp contoured design adds a contemporary touch to any facade.

Specification	
Installation Method:	4" junction box -or- 1/2" EMT conduit
Adjustability:	Fixed
Rating:	Wet

Performance	
CRI / TM-30 (3000K):	90 / Rf: 90 / Rg: 99
LED Maintenance:	L90B10>50,000h
*Down Std Power:	7W
*Down-Up Std Power:	2 x 7W

Delivered Lumens	**2700K**	**3000K**	**3500K**
Mono Down:	612	640	664
Mono Down-Up:	1225	1280	1327

Listing
ETL certified to US and Canadian safety standards.

Warranty
5-year limited warranty.

Ordering

ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: MNO-27SPDUFX-A-PSARMTD8-120

Luminaire	**CCT**	**Downlight***	**Uplight***	**Function**	**Finish**	**Installation**	**Application**	**Controls*****
MNO MONO	**27** 2700K **30** 3000K **35** 3500K	**SP** Standard Power	**DN** Downlight only, no uplight **DU** Downlight with uplight added	**FX** Fixed, Exterior Use	**A** Alu Grey **B** Black **FBRX** Flemish Bronze **N** Anthracite **W** White	**MK** Mud kit into drywall over 4" junction box **PSA** Square coverplate for 4" junction box in Alu Grey finish **PSN** Square coverplate for 4" junction box in Anthracite finish **NA** No optional accessory; utilizing ½" EMT install	**RMT** Remote Power Supply	**D1-UNV** 0-10V Dim 120-277V **D8-120** FE ELV dim 120V **ND-120** Non-Dim 120V


*** Contact factory for additional dimming options.

Related Products

Nocta, Tiga, Montur, Walker II W

Finish Options

MONO DOWN















MONO DOWN-UP















Photometric Data

MONO DOWN



MONO DOWN-UP




Installation Options

REMOTE DRIVER (With Controls D8)

A: 8″ x **B:** 2″-1/2 x **C:** 2″-1/2
A: 203mm x **B:** 64mm x **C:** 64mm


- For Remote application
- ETL Listed
- Damp rated



REMOTE DRIVER (With Controls D1)

A: 8″ x **B:** 2″-3/16 x **C:** 4″-1/4
A: 203mm x **B:** 72mm x **C:** 108mm


- For Remote application
- ETL Listed
- Damp rated



REMOTE DRIVER (With Controls ND)


A: 12″ x **B:** 2″-7/8 x **C:** 4″-1/4
A: 305mm x **B:** 72mm x **C:** 108mm

- For Remote application
- ETL Listed
- Damp rated




Installation Options (cont.)

MK - MUD KIT 1




Requires 4" junction box

PSX - COVERPLATE S 121



ALU GREY or ANTHRACITE
Requires 4" junction box
Used with DOWN (DN)

PSX - COVERPLATE S 122



ALU GREY or ANTHRACITE
Requires 4" junction box
Used with DOWN-UP (DU)

Driver Options

D1

- Dimming Control 0-10V
- Dimming Range 1-100%
- Dim to off yes at 0.7mA
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥87
- THD @ Full Load <20%
- Title 24 Compliant

Dimmer Compatibility

- Leviton IP710-DLZ
- Lutron DVTV-XX
- WattStopper ADF-120277
- Synergy Lighting Controls ISD BC

D8

- Dimming Control Phase Control
- Dimming Range 10-100%
- Dim to off no
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥78
- THD @ Full Load <12%

Dimmer Compatibility

- Leviton IPE04-1LZ
- Lutron DVELV-300P

ND

- Dimming Control NON DIMMABLE
- Power Factor @ Full Load >0.95
- Efficiency @ Full Load ≥90
- THD @ Full Load <10%

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.