



# MONO



Mono is a well-known member of the Delta Light outdoor range. It's been available in LED for a while and now has additional enhancements with the new Mono II. Mono is the first outdoor wall fixture to combine the Delta Light LED array with a lens, resulting in a far-reaching and strongly delineated lighting effect. The Mono's timeless and sharp contoured design adds a contemporary touch to any facade.

Specification	
Adjustability:	Fixed
Rating:	IP54

Performance	
CRI:	90
*Mono SP:	7W
*Mono Down-Up SP:	2 x 7W

Delivered Lumens	2700K	3000K	3500K
Mono:	612Lm	640Lm	664Lm
Mono Down-Up:	1225Lm	1280Lm	1327Lm

#### Listing

ETL certified to US and Canadian safety standards.

#### Warranty

5-year limited warranty.

## Ordering

ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: MNO-SPDN35FX-N-PXINCD1-UNV

Luminaire	Downlight*	Uplight*	CCT	Function	Finish	Installation	Application	Controls***
MNO MONO	SP Standard Power	DN Downlight only, no uplight  DU Downlight with uplight added	27 2700K  30 3000K  35 3500K	FX Fixed, Exterior Use	A Alu Grey  B Black  FBRX Flemish Bronze  N Anthracite  W White	MK Mud kit into drywall over 4" junction box  PX Coverplate for 4" junction box in corresponding finish  NA No optional accessory; utilizing 1/2" EMT install	RMT Remote Power Supply	D1-UNV 0-10V Dim 120-277V  D8-120 FE ELV dim 120V  ND-120 Non-Dim 120V

\*\*\* Contact factory for additional dimming options

## Related Products

Momba, Tiga, Montur, Walker II W

# DELTALIGHT



www.deltalight.com





## Finish Options


### MONO DOWN



ALU GREY




BLACK



FLEMISH BRONZE





ANTHRACITE



WHITE


### MONO DOWN-UP



ALU GREY



BLACK



FLEMISH BRONZE




ANTHRACITE




WHITE

## Photometric Data

### MONO DOWN



### MONO DOWN-UP




## Driver Options

### REMOTE DRIVER

A: 8" x B: 2"-1/2 x C: 2"-1/2  
A: 203mm x B: 64mm x C: 64mm


- For Remote application
- ETL Listed
- Damp rated




### REMOTE DRIVER (With Controls ND)

A: 12" x B: 2"-7/8 x C: 4"-1/4  
A: 305mm x B: 72mm x C: 108mm

- For Remote application
- ETL Listed
- Damp rated




### MK - MUD KIT 1




Requires 4" junction box

### PX - COVERPLATE S 121



DARK GREY or ALU GREY  
Requires 4" junction box  
Used with DOWN (DN)

### PX - COVERPLATE S 122



DARK GREY or ALU GREY  
Requires 4" junction box  
Used with DOWN-UP (DU)



## Driver Options

### D1

- Dimming Control 0-10V
- Dimming Range 1-100%
- Dim to off yes at 0.7mA
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load  $\geq 87$
- THD @ Full Load <20%
- Title 24 Compliant

#### Dimmer Compatibility

- Leviton IP710-DLZ
- Lutron DDTV-XX
- WattStopper ADF-120277
- Synergy Lighting Controls ISD BC

### D8

- Dimming Control Phase Control
- Dimming Range 10-100%
- Dim to off no
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load  $\geq 78$
- THD @ Full Load <12%

#### Dimmer Compatibility

- Leviton IPE04-1LZ
- Lutron DVELV-300P

### ND

- Dimming Control NON DIMMABLE
- Power Factor @ Full Load >0.95
- Efficiency @ Full Load  $\geq 90$
- THD @ Full Load <10%

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.