



SUPERLOOP HC 300 SBL 930

20551 9300 FG



AVAILABLE IN

BLACK 20551 9300 B

FLEMISH BRONZE 20551 9300 FBR

FLEMISH GOLD 20551 9300 FG

WHITE 20551 9300 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	9.7
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL 3 SEGMENTS EXCL.LED POWER SUPPLY 24-DC INCL.6 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.3 x CABLE 2 x 0.75mm ²

Electrical info

ELECTRICAL	24V-DC
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	3 x (LED FLEX FP 45W / CRI>90 / 3000K / 5445lm)
LED TECHNICS (LIGHT SOURCE)	16335 lm // 135 W // 121 lm/W
LED TECHNICS (LUMINAIRE)	7351lm // 155,2W // 47lm/W

Requirements

LED POWER SUPPLY 24V-DC

Options

CABLE BASE R / S

COVERSET R 62-90-100 / S 62-80-90


CONNECTION ST / CONNECTION TRIMLESS

SUSPENSION ST / SUSPENSION TRIMLESS

For detailed installation instructions, please consult the manual : [20551_XXX0_HAND.pdf](#)




FINISH YOUR SPECIFICATION

Current supply

	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

LED power supplies









of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
	300 89 24 80 ED1 LED POWER SUPPLY 24V-DC / 80W DIM1 Dimtype: 1-10V Cutout dimension (mm): 75	1/3 ☐
	300 89 24 150 LED POWER SUPPLY 24V-DC / 150W Dimtype: non-dimmable Cutout dimension (mm): 75	2/3 ☐
	300 89 24 480 LED POWER SUPPLY 24V-DC / 480W DIN Dimtype: non-dimmable	2 ☐

DELTALIGHT

SUPERLOOP HC 300 SBL 930

20551 9300 FG


	<u>300 90 003 ED1</u> 24V-DC / 4A DIM1 UNIT	1/3 ☐
Dimtype: 1-10V		
Cutout dimension (mm): 30		
	<u>300 90 003 ED5</u> 24V-DC / 4A DIM5 UNIT	1/3 ☐
Dimtype: DALI		
Cutout dimension (mm): 30		
	<u>300 90 010</u> 24V-DC / 2 x 4A WIRELESS DIM UNIT	1/3 ☐
Dimtype: WDL = wireless dimmable		
	<u>21012 0111</u> LED POWER SUPPLY 24V-DC / 90W IP67 DIM1	1/3 ☐
Dimtype: 1-10V		
Cutout dimension (mm): 75		
	<u>21012 0121</u> LED POWER SUPPLY 24V-DC / 120W IP67 DIM1	1/3 ☐
Dimtype: 1-10V		
Cutout dimension (mm): 75		
	<u>21012 0145</u> LED POWER SUPPLY 24V-DC / 90W IP67 DIM5	1/3 ☐
Dimtype: DALI		
Cutout dimension (mm): 75		
	<u>21012 0155</u> LED POWER SUPPLY 24V-DC / 120W IP67 DIM5	1/3 ☐
Dimtype: DALI		
Cutout dimension (mm): 75		
	<u>21012 0181</u> LED POWER SUPPLY 24V-DC / 90W DIM1	1/3 ☐
Dimtype: 1-10V		
Cutout dimension (mm): 70		
	<u>21012 0191</u> LED POWER SUPPLY 24V-DC / 120W DIM1	1/3 ☐
Dimtype: 1-10V		
Cutout dimension (mm): 70		
	<u>21012 0225</u> LED POWER SUPPLY 24V-DC / 100W DIM5	1/3 ☐
Dimtype: DALI		
Cutout dimension (mm): 70		

Miscellaneous control equipment

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 90 24 ED2 LED DIMMODULE 24V / 3CH / 6A DIM2

2/3 ☐

Dimtype: DALI or push button

Coversets




204 00 62 ANO COVERSET R 62 ANO

☐

204 00 62 B COVERSET R 62 B

☐

204 00 62 W COVERSET R 62 W

☐


204 00 90 ANO COVERSET R 90 ANO

☐

204 00 90 B COVERSET R 90 B

☐

204 00 90 W COVERSET R 90 W

☐


204 00 100 ANO COVERSET R 100 ANO

☐

204 00 100 B COVERSET R 100 B

☐

204 00 100 W COVERSET R 100 W

☐



204 62 62 ANO COVERSET S 62 ANO

☐


DELTALIGHT

SUPERLOOP HC 300 SBL 930


20551 9300 FG

	<u>204 62 62 B</u>	COVERSET S 62 B	☐
	<u>204 62 62 W</u>	COVERSET S 62 W	☐
	<u>204 80 80 ANO</u>	COVERSET S 80 ANO	☐
	<u>204 80 80 B</u>	COVERSET S 80 B	☐
	<u>204 80 80 W</u>	COVERSET S 80 W	☐
	<u>204 90 90 ANO</u>	COVERSET S 90 ANO	☐
	<u>204 90 90 B</u>	COVERSET S 90 B	☐
	<u>204 90 90 W</u>	COVERSET S 90 W	☐

Suspension parts

	<u>328 10 01</u>	SUSPENSION TRIMLESS O.F.A.	☐
		Cutout dimension (mm): 62 (CONCRETE: 102)	
	<u>15225 0340 B</u>	SUSPENSION ST B	☐
		Cutout dimension (mm): 27	
	<u>15225 0340 W</u>	SUSPENSION ST W	☐

Electric connection parts

	<u>328 10 03</u>	CONNECTION TRIMLESS O.F.A.	☐
		Cutout dimension (mm): 62 (CONCRETE: 102)	

DELTALIGHT

SUPERLOOP HC 300 SBL 930

20551 9300 FG



15225 0360 B CONNECTION ST B

☐

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

☐

Notes: