
DELTALIGHT




M26L - SPY 39 FOCUS 930 DIM5

REFERENCE 23430 9305 BRCU

AVAILABLE IN
BLACK 23430 9305 B
BRUSHED ALU 23430 9305 BRA
BRUSHED ANTHRACITE 23430 9305 BRAT
BRUSHED COPPER 23430 9305 BRCU
BRUSHED GOLD 23430 9305 BRG
BRUSHED OLD BRONZE 23430 9305 BROB
FLEMISH BRONZE 23430 9305 FBR
FLEMISH GOLD 23430 9305 FG
GOLD COLOURED 23430 9305 GC
WHITE 23430 9305 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 360° rotatable
INFORMATION	ADJUSTABLE BEAM 15°-45° EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1018lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	15°-45°
LED TECHNICS (LIGHT SOURCE)	1018lm // 8,6W // 118lm/W
LED TECHNICS (LUMINAIRE)	303lm // 9,9W // 31lm/W

Requirements

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : **23430_XXX5_HAND.pdf**

DELTALIGHT

M26L - SPY 39 FOCUS 930 DIM5

23430 9305 BRCU


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 10

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 24


Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 10

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W — 20


Dimtype: non-dimmable

Cutout dimension (mm): 40


COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)


Available Colours



23358 0000 SLM26L - PROFILE



23358 0010 SLM26L - PROFILE 1m




23358 0020 SLM26L - PROFILE 2m

DELTALIGHT

M26L - SPY 39 FOCUS 930 DIM5

23430 9305 BRCU



23358 0030 SLM26L - PROFILE 3m



Notes: