





M26L - TWEETER BL 930 DIM5

23243 9305 B

AVAILABLE IN
BLACK 23243 9305 B
WHITE 23243 9305 W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 45° swiveling, 355° rotatable
INFORMATION	EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	1067lm // 9,9W // 108lm/W

Remarks	
Take a look at our MAGNETIC PROFILES movie	

Requirements	
BOWL GLASS CLEAR	
BOWL GLASS AMBER	
BOWL GLASS OPAL WHITE	
LED POWER SUPPLY 48V-DC	

For detailed installation instructions, please consult the manual : **23243_XXXX_HAND.pdf**

M26L - TWEETER BL 930 DIM5

23243 9305 B

FINISH YOUR SPECIFICATION



LED power supplies		# of Fixtures
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
171 38 63 300 89 48 90 LED POWER SUPPLY 48V-DC / 90W Dimtype: non-dimmable Cutout dimension (mm): 75	7	
55 100 90 300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: non-dimmable	8	
240 49 60 300 89 48 150 LED POWER SUPPLY 48V-DC / 150W Dimtype: non-dimmable	12	
63 114 125 300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN Dimtype: non-dimmable	19	
17 298 30 21012 0230 LED POWER SUPPLY 48V-DC / 100W Dimtype: non-dimmable Cutout dimension (mm): 40	8	
22 392 30 21012 0240 LED POWER SUPPLY 48V-DC / 200W Dimtype: non-dimmable Cutout dimension (mm): 40	16	

Power box		# of Fixtures
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current




DELTALIGHT

M26L - TWEETER BL 930 DIM5



23243 9305 B

	23377 0010 B SLM26L - POWERBOX 48V-DC / 96W B	8 ☐
Dimtype: non-dimmable		
23377 0010 W SLM26L - POWERBOX 48V-DC / 96W W		8 ☐
	23377 0020 B SLM26L - MID POWERBOX 48V-DC / 96W B	8 ☐
Dimtype: non-dimmable		
23377 0020 W SLM26L - MID POWERBOX 48V-DC / 96W W		8 ☐

To be used with ...

	286 67 01 BOWL GLASS CLEAR	☐
	286 67 02 BOWL GLASS AMBER	☐
	286 67 03 BOWL GLASS OPAL WHITE	☐


COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)	Available Colours
	23358 0000 SLM26L - PROFILE 
	23358 0010 SLM26L - PROFILE 1m 


DELTALIGHT

M26L - TWEETER BL 930 DIM5

23243 9305 B



23358 0020 SLM26L - PROFILE 2m




23358 0030 SLM26L - PROFILE 3m




SHIFTLINE M35R profile


Available Colours




23375 0000 SLM35R - PROFILE



23375 0010 SLM35R - PROFILE 1m



23375 0020 SLM35R - PROFILE 2m



23375 0030 SLM35R - PROFILE 3m



Notes: