



M26L - OCTAV 27 93030 DIM5

29015 9325 B

AVAILABLE IN



BLACK 29015 9325 B

FLEMISH BRONZE 29015 9325 FBR

FLEMISH GOLD 29015 9325 FG

GOLD COLOURED 29015 9325 GC

WHITE 29015 9325 W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 360° rotatable
INFORMATION	REFLECTOR FL-30° EXCLLED POWER SUPPLY 48V-DC SPY 27 L TUBE B included

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	288lm // 6,7W // 43lm/W

Remarks	
Take a look at our MAGNETIC PROFILES movie	

Requirements	
LED POWER SUPPLY 48V-DC	

For detailed installation instructions, please consult the manual : [29015_XXX5_HAND.pdf](#)

M26L - OCTAV 27 93030 DIM5

29015 9325 B

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

15


Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

36

Dimtype: non-dimmable




21012 0230 LED POWER SUPPLY 48V-DC / 100W

15

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W

30


Dimtype: non-dimmable

Cutout dimension (mm): 40


COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)


Available Colours



23358 0000 SLM26L - PROFILE



23358 0010 SLM26L - PROFILE 1m




23358 0020 SLM26L - PROFILE 2m



DELTALIGHT

M26L - OCTAV 27 93030 DIM5

29015 9325 B



23358 0030 SLM26L - PROFILE 3m



Notes: