



OONO W L 927

29613 9200 B

AVAILABLE IN



ALU GREY 29613 9200 A

BLACK 29613 9200 B

FLEMISH BRONZE OUTDOOR 29613 9200 FBRX

ANTHRACITE 29613 9200 N

WHITE 29613 9200 W



[View on website](#)



General info

LOCATION	indoor-outdoor
INSTALLATION	Wall Surface mounted
INGRESS PROTECTION	IP54
PROTECTION AGAINST MECHANICAL IMPACT	IK02
WEIGHT (KG)	4.5
ADJUSTABILITY	non adjustable
INFORMATION	INCL.LED POWER SUPPLY 500mA-DC

Electrical info

ELECTRICAL	100-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 17,2W / CRI>90 (R9: 60) / 2700K / 2009lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	2009lm // 17,2W // 117lm/W
LED TECHNICS (LUMINAIRE)	1064lm // 19,8W // 54lm/W

For detailed installation instructions, please consult the manual : [29613_XXX0_HAND.pdf](#)

Notes:

DELTALIGHT

OONO W L 927

29613 9200 B