

DELTALIGHT



M52 - 2 LED OK 83020 DIM5

REFERENCE 24419 8325





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 45° swiveling
INFORMATION	2 x LENS FL-20° EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 6W / CRI>80 / 3000K / 558lm)
SDCM	SDCM2
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	1116lm // 12W // 94lm/W
LED TECHNICS (LUMINAIRE)	948lm // 13,8W // 69lm/W

Requirements

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : **24419_8X25_HAND.pdf**

DELTALIGHT

M52 - 2 LED OK 83020 DIM5

24419 8325


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

Min current | Max current


ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 89 48 90 LED POWER SUPPLY 48V-DC / 90W — 6


Dimtype: non-dimmable

Cutout dimension (mm): 75




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 7

Dimtype: non-dimmable




300 89 48 150 LED POWER SUPPLY 48V-DC / 150W — 10

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 17


Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 7

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W — 14


Dimtype: non-dimmable

Cutout dimension (mm): 40

COMPATIBLE COMPOSABLES

SPLITLINE M52 profile

Available Colours




420 52 10 00 SPM52 - PROFILE 1m


DELTALIGHT

M52 - 2 LED OK 83020 DIM5


24419 8325



420 52 20 00 SPM52 - PROFILE 2m



420 52 30 00 SPM52 - PROFILE 3m



24413 0000 SPM52 - PROFILE

Notes: