
DELTALIGHT




CONFORM P20 PDS DOWN-UP 953067

REFERENCE 26515 7320 W-B

AVAILABLE IN
BLACK-BLACK 26515 7320 B-B
BLACK-FLEMISH GOLD 26515 7320 B-FG
WHITE-BLACK 26515 7320 W-B





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	5.6
ADJUSTABILITY	non adjustable
INFORMATION	84 x REFLECTOR FL-67° (DOWN) INCL.DIMMABLE LED POWER SUPPLY 900mA-DC DOWN / 700mA-DC UP INCL.PRESENCE & DAYLIGHT SENSOR INCL.2 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 3 x 0.75mm² NATURAL LIGHT TECHNOLOGY

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 30,5W / CRI>95 (R9: 80) / 3000K / 3570lm UP: LED cluster 23,1W / CRI>95 (R9: 80) / 3000K / 2842lm
TM-30 VALUES	Rf: 94 / Rg: 103
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	DOWN: 3570lm // 30,5W // 117lm/W UP: 2842lm // 23,1W // 123lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 2242lm // 35,1W // 64lm/W UP: 2239lm // 26,6W // 84lm/W

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS

DELTALIGHT



CONFORM P20 PDS DOWN-UP 953067

26515 7320 W-B



For detailed installation instructions, please consult the manual : **26515_XXX0_HAND.pdf**

FINISH YOUR SPECIFICATION

Current supply

	**203 99 55 ANO**	CABLE BASE R ANO
	203 99 55 B	CABLE BASE R B
	203 99 55 W	CABLE BASE R W
	**203 99 56 ANO**	CABLE BASE S ANO
	203 99 56 B	CABLE BASE S B
	203 99 56 W	CABLE BASE S W





Coversets

	**204 00 62 ANO**	COVERSET R 62 ANO
	204 00 62 B	COVERSET R 62 B
	204 00 62 W	COVERSET R 62 W
	**204 00 90 ANO**	COVERSET R 90 ANO

DELTALIGHT

CONFORM P20 PDS DOWN-UP 953067

26515 7320 W-B


	204 00 90 B	COVERSET R 90 B	☐
	204 00 90 W	COVERSET R 90 W	☐
	**204 00 100 ANO**	COVERSET R 100 ANO	☐
	204 00 100 B	COVERSET R 100 B	☐
	204 00 100 W	COVERSET R 100 W	☐
	**204 62 62 ANO**	COVERSET S 62 ANO	☐
	204 62 62 B	COVERSET S 62 B	☐
	204 62 62 W	COVERSET S 62 W	☐
	**204 80 80 ANO**	COVERSET S 80 ANO	☐
	204 80 80 B	COVERSET S 80 B	☐
	204 80 80 W	COVERSET S 80 W	☐
	**204 90 90 ANO**	COVERSET S 90 ANO	☐
	204 90 90 B	COVERSET S 90 B	☐
	204 90 90 W	COVERSET S 90 W	☐

DELTALIGHT

CONFORM P20 PDS DOWN-UP 953067


26515 7320 W-B

Suspension parts



328 10 01 SUSPENSION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)




15225 0340 B SUSPENSION ST B

Cutout dimension (mm): 27

15225 0340 W SUSPENSION ST W

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)




15225 0360 B CONNECTION ST B


Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

Other



26510 0010 PDS REMOTE CONTROL



26510 0020 PDS SENSOR PROGRAMMER

CONFORM P20 PDS DOWN-UP 953067

26515 7320 W-B

Notes: