
DELTALIGHT




COMPO M 92710

REFERENCE 9 15727 9210 W

AVAILABLE IN
BLACK 9 15727 9210 B
CHROMED 9 15727 9210 C
DARK CHROMED 9 15727 9210 DC
WHITE 9 15727 9210 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 110
RECESSED DEPTH (MM)	105
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.256
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable
INFORMATION	Accessories are not applicable with Super Spot except Honeycomb Single use B Super spot with Dali Dim max current rating 1750mA

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	G

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 4,6-5,7W / CRI>90 / 2700K / 347-389lm
BEAMANGLE	10°
LED TECHNICS (LIGHT SOURCE)	389lm // 5,7W // 68lm/W
LED TECHNICS (LUMINAIRE)	318lm // 6,6W // 49lm/W

Requirements

LED POWER SUPPLY 700 mA - DC

Accessories

COMPO M HONEYCOMB SINGLE USE B
COMPO M LINEAR SPREAD LENS
COMPO M SPREAD LENS
COMPO M SOFTENING LENS
COMPO M GLASS SBL

For detailed installation instructions, please consult the manual : **9_15727_XXX0_HAND.pdf**

DELTALIGHT

COMPO M 92710

9 15727 9210 W

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 **System ceiling**	15710 0020 - MOUNTING KIT COMPO M TRIM	Required
	15710 0050 - MOUNTING KIT COMPO M TRIMLESS	Required
 **Plasterboard**	15710 0020 - MOUNTING KIT COMPO M TRIM	Required
	15710 0050 - MOUNTING KIT COMPO M TRIMLESS	Required
 **Wood**	15710 0020 - MOUNTING KIT COMPO M TRIM	Required
	15710 0050 - MOUNTING KIT COMPO M TRIMLESS	Required

FINISH YOUR SPECIFICATION

LED Power supply

of Fixtures

of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current


15710 3100	LED POWER SUPPLY 18W NO DIM 1400mA	1->4
15710 3500	LED POWER SUPPLY MULTIPOWER 15W NO DIM 700mA	1
15710 4000	LED POWER SUPPLY MULTIPOWER 15W DIM8 700mA	1
15710 4900	LED POWER SUPPLY MULTIPOWER 20W DIM1 700mA	1
15710 5000	LED POWER SUPPLY MULTIPOWER 55W DALI DT6 1400mA	1->13

Dimtype: DALI

15710 5600	LED POWER SUPPLY MULTIPOWER 20W DALI DT6 700mA	1

Dimtype: DALI

Mounting kits



15710 0020 B MOUNTING KIT COMPO M TRIM B

Cutout dimension (mm): 76

15710 0020 W MOUNTING KIT COMPO M TRIM W

DELTALIGHT

COMPO M 92710

9 15727 9210 W



15710 0050 MOUNTING KIT COMPO M TRIMLESS

Cutout dimension (mm): 76

Light altering devices

15710 1100 B COMPO M HONEYCOMB SINGLE USE B

15710 1110 COMPO M LINEAR SPREAD LENS

Cutout dimension (mm): 32,5

15710 1120 COMPO M SPREAD LENS

Cutout dimension (mm): 32,5

15710 1130 COMPO M SOFTENING LENS

Cutout dimension (mm): 32,5

15710 1140 COMPO M GLASS SBL

Cutout dimension (mm): 32,5

Notes: