



## OML50 - PRISMATIC LENS DU HE 2296mm 940 DIM5

31644 9405 B

BESCHIKBAAR IN  
**ZWART** 31644 9405 B

 [Bekijk op website](#)



### Algemene info

<b>LOCATIE</b>	binnen
<b>STOF EN WATERDICHTHEID</b>	IP20
<b>GEWICHT (KG)</b>	3.1
<b>INFO</b>	INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT

### Elektrische info

<b>INGANGSSPANNING</b>	220-240V / 0 50-60Hz
<b>KLASSE</b>	I
<b>VOEDING</b>	YES
<b>DIM TYPE</b>	DALI
<b>ENERGIE KLASSE</b>	D
<b>CERTIFICATEN</b>	EPD, RCM

### Info lichtbron

<b>LIGHTSOURCE NAME</b>	LED
<b>LICHTBRON</b>	DOWN: LED cluster 34,1W / CRI>90 (R9: 50) / 4000K / 5821lm UP: LED cluster 28,6W / CRI>90 (R9: 50) / 4000K / 4626lm
<b>TM-30-15 WAARDEN</b>	Rf: 90 / Rg: 101
<b>SDCM</b>	SDCM3
<b>RISK-GROEP</b>	RG1
<b>LM80</b>	L80 > 60000
<b>LED TECHNIEK (LICHTBRON)</b>	DOWN: 5821lm // 34,1W // 171lm/W UP: 4626lm // 28,6W // 162lm/W

### Opties

WIRELESS CONTROL DIM5

Notes: