





Image may differ from the actual product
Consult drawing for correct size and structure

INFORM 40 SQ 320 DOWN 94063 DIM5

30716 9435 B-B

AVAILABLE IN
BLACK-BLACK 30716 9435 B-B
WHITE-BLACK 30716 9435 W-B



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	5
ADJUSTABILITY	non adjustable
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI DT6) Power selection to be set on driver EXCL.CABLE SUSPENSION

Electrical info

ELECTRICAL CLASS	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	HO: LED cluster 48,4W / CRI>90 (R9: 50) / 4000K / 7283lm Or LED cluster 32,6W / CRI>90 (R9: 50) / 4000K / 5286lm
TM-30 VALUES	Rf: 90 / Rg: 101 rf: 90 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	63°
LED TECHNICS (LIGHT SOURCE)	HO: 7283lm // 48,4W // 151lm/W Or 5286lm // 32,6W // 162lm/W
LED TECHNICS (LUMINAIRE)	HO: 5039lm // 55,7W // 91lm/W Or 3657lm // 37,5W // 98lm/W

Options

INF40 SQ 320/360 - SUSPENSION SET
CABLE BASE R / S

DELTALIGHT

INFORM 40 SQ 320 DOWN 94063 DIM5

30716 9435 B-B

For detailed installation instructions, please consult the manual : [30716_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply



203 99 55 ANO CABLE BASE R ANO

203 99 55 B CABLE BASE R B

203 99 55 W CABLE BASE R W



203 99 56 ANO CABLE BASE S ANO

203 99 56 B CABLE BASE S B

203 99 56 W CABLE BASE S W

Fixation components



30710 0020 B INF40 SQ 320/360 - SUSPENSION SET 1,6m B

30710 0020 W INF40 SQ 320/360 - SUSPENSION SET 1,6m W



30710 0040 B INF40 SQ 320/360 - SUSPENSION SET 3,0m B

30710 0040 W INF40 SQ 320/360 - SUSPENSION SET 3,0m W

DELTALIGHT

INFORM 40 SQ 320 DOWN 94063 DIM5

30716 9435 B-B

Notes: