



LOGIC LINEAR ON 880 92740 DIM5

30835 9235 N

AVAILABLE IN



ALU GREY 30835 9235 A

BLACK 30835 9235 B

FLEMISH BRONZE OUTDOOR 30835 9235 FBRX

ANTHRACITE 30835 9235 N

WHITE 30835 9235 W



[View on website](#)



General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted, Wall Surface mounted
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK07
WEIGHT (KG)	2
INFORMATION	16 x LENS WFL-40° EXCL. LED POWER SUPPLY 48V-DC DALI DT8 dimming
Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	CB, ENEC
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 28,8W / CRI>90 (R9: 55) / 2700K / 3288lm
TM-30 VALUES	Rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	3288lm // 28,8W // 111lm/W
LED TECHNICS (LUMINAIRE)	2502lm // 33,1W // 76lm/W

Requirements



WALL BRACKET SET
FLOOR BRACKET SET
IP68 CABLE + CONNECTOR 5P
LED POWER SUPPLY 48V-DC

Options

THROUGH WIRING SET IP68

For detailed installation instructions, please consult the manual : [30835_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
		Min current Max current
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		
 21032 0390 LED POWER SUPPLY 48V-DC / 90W Dimtype: non-dimmable Cutout dimension (mm): 75	2	
Fixation components		
 30810 0040 LOGIC LINEAR 880 BOX EXTEND		
30810 0040 INOX WALL BRACKET SET 60 INOX		
30810 0040 N WALL BRACKET SET 60 N		
 30810 0050 INOX WALL BRACKET SET 100 INOX		
30810 0050 N WALL BRACKET SET 100 N		
 30810 0060 INOX WALL BRACKET SET 200 INOX		
30810 0060 N WALL BRACKET SET 200 N		

DELTALIGHT

LOGIC LINEAR ON 880 92740 DIM5

30835 9235 N



30810 0070 INOX FLOOR BRACKET SET INOX

☐

Electric connection parts



30810 0080 IP68 CABLE + CONNECTOR 5P - 0,5m

☐

30810 0090 IP68 CABLE + CONNECTOR 5P - 2m

☐

30810 0110 THROUGH WIRING SET IP68 880

☐

Notes: