
DELTALIGHT




SPYCO 90 93024 ADM

REFERENCE 19921 9320 B

AVAILABLE IN
BLACK 19921 9320 B
FULL WHITE 19921 9320 FW





View on website

General info	
LOCATION	indoor
INSTALLATION	Mains voltage track Mains voltage track mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.8
ADJUSTABILITY	0° to 90° swiveling, 350° rotatable
INFORMATION	INCL.LED POWER SUPPLY 800/900mA-DC Max. 800mA with HONEYCOMB

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	F
CERTIFICATES	EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	@ 900mA: LED array 33,2W / CRI>90 (R9: 52) / 3000K / 3465lm Or @ 800mA (+HONEYCOMB): LED array 29,1W / CRI>90 (R9: 52) / 3000K / 3144lm
MIN. DISTANCE TO LIGHTSOURCE (M)	1
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	24°
LED TECHNICS (LIGHT SOURCE)	@ 900mA: 3465lm // 33,2W // 104lm/W Or @ 800mA (+HONEYCOMB): 3144lm // 29,1W // 108lm/W
LED TECHNICS (LUMINAIRE)	@ 900mA: 3099lm // 38,2W // 81lm/W Or @ 800mA (+HONEYCOMB): 2075lm // 33,5W // 62lm/W

Requirements

TRACK 3F ON

Accessories

SPYCO 90 HONEYCOMB

DELTALIGHT

SPYCO 90 93024 ADM

19921 9320 B

For detailed installation instructions, please consult the manual : **19921_XXX0_HAND.pdf**

FINISH YOUR SPECIFICATION

Light altering devices



19922 0020 B SPYCO 90 HONEYCOMB B

COMPATIBLE TRACKS

TRACK 3F ON			Available Colours
28900 0020 TRACK 3F ON 2m	2000 m	1.8 kg	
28900 0030 TRACK 3F ON 3m	3000 m	2.7 kg	

Notes: