


MOUNTING KIT SIDE AIR 101

29810 0010



[View on website](#)



General info

LOCATION	indoor
CUTOUT SHAPE/SIZE (MM)	round - 168
RECESSED DEPTH (MM)	160
THICKNESS OF MOUNTING SURFACE (MM)	max.12,5
WEIGHT (KG)	0.29
INFORMATION	Supply flow rate: max. 25m ³ /h Extraction flow rate: max. 50m ³ /h For flexible tubes Ø100mm

For detailed installation instructions, please consult the manual : [29810_0010_HAND.pdf](#)

WHERE USED

202 144 811 922	DEEP RINGO TRIMLESS LED 92733
202 144 811 932	DEEP RINGO TRIMLESS LED 93033
202 144 1902	DEEP RINGO TRIMLESS LED 9-SOFT
202 146 811 922	DEEP RINGO TRIMLESS LED IP 92733
202 146 811 932	DEEP RINGO TRIMLESS LED IP 93033
19436 9030	DEEP RINGO TRIMLESS SOFT 93045
19441 9220	DEEP RINGO TRIMLESS HE 92720
19441 9230	DEEP RINGO TRIMLESS HE 92740
19441 9320	DEEP RINGO TRIMLESS HE 93020
19441 9330	DEEP RINGO TRIMLESS HE 93040
19441 9420	DEEP RINGO TRIMLESS HE 94020
19441 9430	DEEP RINGO TRIMLESS HE 94040

Notes: