
DELTALIGHT



MOUNTING KIT SIDE AIR 101

REFERENZEN 29810 0010



Auf der Website anzeigen

Allgemeine Information	
ANWENDUNGSBEREICH	innenbereich
FORM / GRÖSSE DES AUSSCHNITTS (MM)	rund - 168
EINBAUTIEFE (MM)	160
DICKE DER BEFESTIGUNGSFLÄCHE (MM)	max.12,5
GEWICHT (KG)	0.29
INFORMATION	Supply flow rate: max. 25m³/h Extraction flow rate: max. 50m³/h For flexible tubes Ø100mm

Detaillierte Installationsanweisungen finden Sie in der Montageanleitung : **29810_0010_HAND.pdf**

WO VERWENDET

202 144 811 922	DEEP RINGO TRIMLESS LED 92733
202 144 811 932	DEEP RINGO TRIMLESS LED 93033
202 144 1902	DEEP RINGO TRIMLESS LED 9-SOFT
202 146 811 922	DEEP RINGO TRIMLESS LED IP 92733
202 146 811 932	DEEP RINGO TRIMLESS LED IP 93033
19436 9030	DEEP RINGO TRIMLESS SOFT 93045
19441 9220	DEEP RINGO TRIMLESS HE 92720
19441 9230	DEEP RINGO TRIMLESS HE 92740
19441 9320	DEEP RINGO TRIMLESS HE 93020
19441 9330	DEEP RINGO TRIMLESS HE 93040
19441 9420	DEEP RINGO TRIMLESS HE 94020
19441 9430	DEEP RINGO TRIMLESS HE 94040

Notes:

Delta Light NV may revise the information and technical data at any time without notice. Version: 09/10/2026