



DEEP RINGO TRIMLESS HE 94020

REFERENCE

19441 9420 BROB

AVAILABLE IN

BLACK 19441 9420 B
BRUSHED ALU 19441 9420 BRA
BRUSHED ANTHRACITE 19441 9420 BRAT
BRUSHED BROWN BRONZE 19441 9420 BRBB
BRUSHED COPPER 19441 9420 BRCU
BRUSHED GOLD 19441 9420 BRG
BRUSHED OLD BRONZE 19441 9420 BROB
CREAM 19441 9420 CR
FLEMISH BRONZE 19441 9420 FBR
FLEMISH GOLD 19441 9420 FG
GOLD COLOURED 19441 9420 GC
PIANO BLACK 19441 9420 PB
WHITE 19441 9420 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - Ø KIT
RECESSED DEPTH (MM)	95
INGRESS PROTECTION	IP23/20
WEIGHT (KG)	0.3
ADJUSTABILITY	non adjustable
INFORMATION	LENS FL-20° EXCL.LED POWER SUPPLY 350mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	D
CERTIFICATES	EPD, LCA

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 60) / 4000K / 975lm
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	975lm // 6W // 163lm/W
LED TECHNICS (LUMINAIRE)	834lm // 6,9W // 121lm/W

Remarks

High Efficacy : > 100lm/W

Requirements

MOUNTING KIT R82 TRIMLESS O.F.A.
MOUNTING KIT AIR 101
LED POWER SUPPLY 350mA-DC DIM (Remote)

DEEP RINGO TRIMLESS HE 94020

19441 9420 BROB


For detailed installation instructions, please consult the manual : [19441_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 System ceiling	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Plasterboard	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Stucanet	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Concrete + plaster	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Lintel + plaster	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Hollow-core slab + plaster	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
	 29810 0100 - MOUNTING KIT SIDE AIR ONLY 1	Required
	 29810 0050 - MOUNTING KIT NO AIR 101	Required
	 29810 0010 - MOUNTING KIT SIDE AIR 101	Required
	 29810 0210 - MOUNTING KIT TOP AIR 101	Required
	 29810 0050 - MOUNTING KIT NO AIR 101	Required
	 29810 0200 - MOUNTING KIT TOP AIR ONLY 1	Required
 Cold stretched ceiling	 15212 0070 - MOUNTING KIT R82 TRIMLESS CSC	Required
 Warm stretched ceiling	 15212 0150 - MOUNTING KIT R82 TRIMLESS WSC	Required

FINISH YOUR SPECIFICATION

Emergency units



21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B



Cutout dimension (mm): 27

DELTA LIGHT

DEEP RINGO TRIMLESS HE 94020

19441 9420 BROB

21032 0270 W

EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

LED power supplies		# of Fixtures
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
34 19 115	300 90 91 LED POWER SUPPLY 350mA-DC / 15W Dimtype: non-dimmable Cutout dimension (mm): 40	2(1)
21 102 39	300 90 110 LED POWER SUPPLY 350mA-DC / 10W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 42	1
122 118 52	300 90 116 LED POWER SUPPLY 350mA-DC / 18W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 55	2->2
122 118 52	21012 0515 LED POWER SUPPLY MULTI POWER DIM5 Dimtype: DALI Cutout dimension (mm): 55	1(1)
122 68 42	21012 0520 LED POWER SUPPLY 350mA-DC / 8W Dimtype: non-dimmable Cutout dimension (mm): 47	1(0)
122 118 52	21012 0575 LED POWER SUPPLY MULTI POWER DIM5 Dimtype: DALI Cutout dimension (mm): 55	2->3(2)


Mounting kits		
97 73 138 45	15212 2000 MOUNTING KIT R82 TRIMLESS O.F.A. Cutout dimension (mm): 105	

DELTALIGHT

DEEP RINGO TRIMLESS HE 94020

19441 9420 BROB

Mounting kits stretched ceiling




15212 0070 MOUNTING KIT R82 TRIMLESS CSC

☐

15212 0150 MOUNTING KIT R82 TRIMLESS WSC

☐

Mounting kits side air + light




29810 0010 MOUNTING KIT SIDE AIR 101

Cutout dimension (mm): 168

☐

Mounting kits top air + light




29810 0210 MOUNTING KIT TOP AIR 101

Cutout dimension (mm): 135

☐

Mounting kits side air only




29810 0100 MOUNTING KIT SIDE AIR ONLY 1

Cutout dimension (mm): 168

☐

Mounting kits top air only



29810 0200 MOUNTING KIT TOP AIR ONLY 1

Cutout dimension (mm): 135


☐

DELTALIGHT

DEEP RINGO TRIMLESS HE 94020

19441 9420 BROB

Mounting kits no air



29810 0050 MOUNTING KIT NO AIR 101



Cutout dimension (mm): 168

Notes: