



OML50 - PRISMATIC LENS DU HE
2624mm 930

31645 9300 B

BESCHIKBAAR IN
ZWART 31645 9300 B

 [Bekijk op website](#)



Algemene info	
LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	3.5
INFO	INCL LED POWER SUPPLY CABLING 1 CIRCUIT
Elektrische info	
INGANGSSPANNING	220-240V / 0 50-60Hz
KLASSE	I
VOEDING	YES
DIM TYPE	niet dimbaar
ENERGIE KLASSE	D
CERTIFICATEN	EPD, RCM
Info lichtbron	
LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 39W / CRI>90 (R9: 50) / 3000K / 6384lm UP: LED cluster 32,6W / CRI>90 (R9: 50) / 3000K / 5069lm
TM-30-15 WAARDEN	Rf: 92 / Rg: 100
SDCM	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	DOWN: 6384lm // 39W // 164lm/W UP: 5069lm // 32,6W // 155lm/W

Notes: