



SPY C & MICROSPY C



Despite its minimalistic appearance, Spy C wows you with its powerful and striking light effect. As a pendant, its slenderness allows you to create playful or humble set-ups by grouping multiple luminaires or choosing a single pendant.

Specification	Size 39	Size 63
LED Aperture	1 ⁵ / ₁₆ "	2 ⁵ / ₁₆ "
Installation Method:	4" junction box	
Adjustability:	Fixed	
Rating:	Damp (EU IP20)	

Performance	
CRI / TM-30 (3000K):	90 / Rf: 90 / Rg: 99
McAdam Step:	1
LED Maintenance:	L90B10>50,000h
*Standard Power:	6.7W
¹ Remote Power Supply Capacity (# luminaires):	D1-UNV min1-max2 D8-120 min1-max1

Delivered Lumens	2700K		3000K		3500K	
**Optic:	MD	WS	MD	WS	MD	WS
Microspy 39 C:		507		530		549
Spy 63 C:	387		404		419	

Listing

ETL certified to US and Canadian safety standards.

Warranty

5-year limited warranty.

Ordering

ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: SPY6303-30MDSP-W-FG-PCCRINCD8-120

Luminaire	Size	Length	CCT	Optic**	Power*	Finish	Inner Finish	Type	Installation	Application	Controls***
SPY SPY C	39 38mm / 1 ¹ / ₂ " Diameter (MICROSPY C)	04 400mm 15 ³ / ₄ "	27 2700K	WS Medium Wide Spot 45°	SP Standard Power	B Black W White	NA No inner finish	PC Pendant, 5' cord suspended	PR Round coverplate for 4" junction box (matches selected Finish)	RMT ¹ Remote Power Supply	D1-UNV 0-10V dim 120-277V D8-120 FE ELV dim 120V
			30 3000K								
			35 3500K								
	63 63mm / 2 ¹ / ₂ " Diameter (SPY C)	03 300mm 11 ¹³ / ₁₆ "	27 2700K	MD Medium Spot 33°	SP Standard Power	B Black W White	B Black FBR Flemish Bronze FG Flemish Gold MMAT Gold Matte SG Silver Grey W White	PC Pendant, 5' cord suspended	CR Round surface canopy with integrated coverplate for 4" junction box (matches selected Finish)	INC Integral Power Supply	D8-120 FE ELV dim 120V
			30 3000K								
			35 3500K								

¹ Remote power supply capacity noted in table above.
*** Contact factory for Dali, DMX, or other dimming options.

Related Products

Spy 27, Spy 39, Spy 52, Spy 66, Spy 90, Spy Focus, Spy S

DELTALIGHT


www.deltalight.com






Finish Options

MICROSPY 39 C WITH BLACK INNER FINISH



SPY 63 C



INNER FINISH - Only available with Size 63



Accessories

Only available with Size 63




GLASS SBL 50
- 413 03 05



HONEYCOMB 50
- 413 03 01 B




LINEAR SPREAD LENS 50
- 413 03 02



SOFTENING LENS 50
- 413 03 04




SPREAD LENS 50
- 413 03 03



SBL
LIGHT EFFECT




HONEYCOMB
LIGHT EFFECT



LINEAR SPREAD LENS
LIGHT EFFECT



SOFTENING LENS
LIGHT EFFECT




SPREAD LENS
LIGHT EFFECT




Photometric Data

MICROSPY 39 C



SPY 63 C




Installation Options

REMOTE DRIVER (With Controls D8)

A: 8" x B: 2"-1/2 x C: 2"-1/2
A: 203mm x B: 64mm x C: 64mm


- For Remote application
- ETL Listed
- Damp rated



REMOTE DRIVER (With Controls D1)

A: 8" x **B:** 2"-3/16 x **C:** 4"-1/4
A: 203mm x **B:** 72mm x **C:** 108mm

- For Remote application
- ETL Listed
- Damp rated



Driver Options

D1

- | | |
|----------------------------|---|
| • Dimming Control | 0-10V |
| • Dimming Range | 1-100% |
| • Dim to off | yes at 0.8V, 1V, 1.2V, or N/A |
| • Power Factor @ Full Load | >0.9 under 120Vac Input with 80~100% load condition (for all output currents) |
| • Efficiency @ Full Load | ≥86 |
| • THD @ Full Load | <20% under 120Vac input with 80~100% load condition (for all output currents) |

Dimmer Compatibility

- Leviton IP710-LFZ / IP710-DLX
- Lutron DVTV/DVSTV/DVSCTV/DVSCSTV

D8

- | | |
|----------------------------|---------------|
| • Dimming Control | Phase Control |
| • Dimming Range | 10-100% |
| • Dim to off | no |
| • Power Factor @ Full Load | >0.9 |
| • Efficiency @ Full Load | ≥80 |
| • THD @ Full Load | <5% |

Dimmer Compatibility

- Leviton IPE04-1LZ
- Lutron DVELV-300P

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.