


SOLI - LINE 110 DOWN 930 MDL

27151 9300 B

AVAILABLE IN
BLACK 27151 9300 B
WHITE 27151 9300 W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 48V-DC
Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	E
CERTIFICATES	CB, ENEC
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED flex 23,4W / CRI>90 (R9: 65) / 3000K / 3000lm
SDCM	SDCM3
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	3000lm // 23,4W // 128lm/W
LED TECHNICS (LUMINAIRE)	2004lm // 26,9W // 74lm/W
Requirements	
LED POWER SUPPLY 48V-DC	
Options	
DIMMABLE MODULATOR	

For detailed installation instructions, please consult the manual : [27151_XXX0_HAND.pdf](#)

SOLI - LINE 110 DOWN 930 MDL

27151 9300 B

FINISH YOUR SPECIFICATION


SMART 48

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9

7

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD

7

Dimtype: WDL = wireless dimmable


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

3


Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

9

Dimtype: non-dimmable




21012 0230 LED POWER SUPPLY 48V-DC / 100W

3

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W

7

Dimtype: non-dimmable



Cutout dimension (mm): 40

DELTALIGHT

SOLI - LINE 110 DOWN 930 MDL

27151 9300 B

COMPATIBLE COMPOSABLES

SOLISCAPE profile	Available Colours
 27111 0020 SOLI - PROFILE 2m	
 27111 0030 SOLI - PROFILE 3m	

Notes: