



LOGIC LINEAR 880 93040

30820 9330 INOX

AVAILABLE IN
INOX 30820 9330 INOX



 [View on website](#)



General info	
LOCATION	outdoor
INSTALLATION	Floor Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - BOX
RECESSED DEPTH (MM)	140
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK09
WEIGHT (KG)	4.4
ADJUSTABILITY	non adjustable
INFORMATION	16 x LENS WFL-40° INCL.LED POWER SUPPLY 650mA-DC INCL.1 x CABLE H05 RN-F 3 x 0.75mm² 0,5m INCL.IP68 CONNECTOR 3P ESG 8mm max.500kg
Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 28,8W / CRI>90 (R9: 60) / 3000K / 3597lm
TM-30 VALUES	Rf: 92 / Rg: 99
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	3597lm // 28,8W // 121lm/W
LED TECHNICS (LUMINAIRE)	2400lm // 33,1W // 72lm/W
Requirements	
LOGIC LINEAR BOX	

For detailed installation instructions, please consult the manual : [30820_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Ground mounting boxes



30810 0030 LOGIC LINEAR 880 BOX

Cutout dimension (mm): 920 x 150

☐

Waterproof connection parts



431 99 02 IP68 JUNCTION BOX 4P

☐

21034 0150 IP68 Y-CONNECTOR 5P

☐

Notes: