
DELTALIGHT




# LOGIC LINEAR 880 94015

**REFERENCE** 30820 9410 INOX

AVAILABLE IN
**INOX** 30820 9410 INOX




View on website

| General info | |
|---|---|
| **LOCATION** | outdoor |
| **INSTALLATION** | Floor Recessed |
| **CUTOUT SHAPE/SIZE (MM)** | rectangle - BOX |
| **RECESSED DEPTH (MM)** | 140 |
| **INGRESS PROTECTION** | IP67 |
| **PROTECTION AGAINST MECHANICAL IMPACT** | IK09 |
| **WEIGHT (KG)** | 4.4 |
| **ADJUSTABILITY** | non adjustable |
| **INFORMATION** | 16 x LENS SP-15°<br>INCL.LED POWER SUPPLY 650mA-DC<br>INCL.1 x CABLE H05 RN-F 3 x 0.75mm² 0,5m<br>INCL.IP68 CONNECTOR 3P<br>ESG 8mm max.500kg |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 220-240V / 0\|50-60Hz |
| **CLASS** | I |
| **POWER SUPPLY** | YES |
| **DIM TYPE** | non-dimmable |
| **ENERGY CLASS** | E |
| **CERTIFICATES** | CB, ENEC, EPD, RCM |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED cluster 28,8W / CRI>90 (R9: 64) / 4000K / 3898lm |
| **TM-30 VALUES** | Rf: 91 / Rg: 100 |
| **SDCM** | SDCM3 |
| **RISKGROUP** | RG2 |
| **LM80** | L80 > 150000 |
| **BEAMANGLE** | 15° |
| **LED TECHNICS (LIGHT SOURCE)** | 3898lm // 28,8W // 131lm/W |
| **LED TECHNICS (LUMINAIRE)** | 2885lm // 33,1W // 87lm/W |

**Requirements**

LOGIC LINEAR BOX

For detailed installation instructions, please consult the manual : **30820_XXX0_HAND.pdf**


DELTALIGHT

# LOGIC LINEAR 880 94015

30820 9410 INOX

## FINISH YOUR SPECIFICATION


### Ground mounting boxes





**30810 0030** LOGIC LINEAR 880 BOX ☐

**Cutout dimension (mm): 920 x 150**

### Waterproof connection parts




**431 99 02** IP68 JUNCTION BOX 4P ☐




**21034 0150** IP68 Y-CONNECTOR 5P ☐

Notes: