# TOPIX



This multi award-winning luminaire ensures a playful light and gives you a lot of freedom. So you can put together an attractive or artistic cluster of light by combining multiple devices. You can also choose the color of the light: warm white or cool white. The fixture itself, which is semi recessed and semi surface, is available in aluminium grey or white.

| Specification | CF / CL | MK | NA |
|---|---|---|---|
| Installation Method (Interior): | Concrete | 4" junction box | |
| Wall Thickness (Interior): | 2 5/16" | ½" or ⅝" drywall | |
| Installation Method (Exterior): | | 4" junction box | ½" EMT conduit |
| Wall Thickness (Exterior): | | ½" or ⅝" drywall | Any |
| Adjustability: | Fixed | | |
| Rating: | Damp -or- Wet | | |

| Performance | Interior | Exterior |
|---|---|---|
| CRI / TM-30 (3000K): | 80 / Rf: 86 / Rg: 95 | 90 |
| SDCM: | 3 | |
| LED Maintenance: | L90B10>150,000h | |
| *Standard Power (SP): | 2 x 1.2W | 2 x 3.4W |
| [1]Remote Power Supply Capacity (# luminaires) SP: | D1-UNV min4-max15<br>D8-120 min3-max9 | |

| Delivered Lumens | 3000K | |
|---|---|---|
| Topix: | 34 | 225 |

**Listing**
ETL certified to US and Canadian safety standards.

**Warranty**
5-year limited warranty.

## Ordering
ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: TPX-SP30FXL-G-NAINCND-120

| Luminaire | Power* | CCT | Function | Style | Finish | Installation | Application | Controls*** |
|---|---|---|---|---|---|---|---|---|
| **TPX**<br>TOPIX | **SP**<br>Standard Power | **30**<br>3000K | **FI**<br>Fixed, Interior use | **O**<br>Open | **A**<br>Alu Grey | **CF**<br>For concrete with flange | **RMT**[1]<br>Remote Power Supply | **D1-UNV**<br>0-10V dim 120-277V |
| | | | | | **W**<br>White | **CL**<br>For concrete without flange | | **D1-347**<br>0-10V dim 347V |
| | | | | | | **MK**<br>Mud kit into ½" or ⅝" drywall over 4" junction box | | **D8-120**<br>FE ELV dim 120V |
| | | | **FX**<br>Fixed, Exterior use | **L**<br>Lensed | **A**<br>Alu Grey | **MK**<br>Mud kit into ½" or ⅝" drywall over 4" junction box | **INC**<br>Integral Power Supply | **ND-120**<br>Non-dim 120V |
| | | | | | **G**<br>Grey Brown | **NA**<br>No optional accessory; utilizing ½" EMT conduit | | |


1 Remote power supply capacity noted in table above.
*** Contact factory for Dali, DMX, or other dimming options.

## Related Products

**Nocta (alt style), Tiga (alt style)**

## Finish Options

### TOPIX INTERIOR






ALU GREY


WHITE

### TOPIC EXTERIOR (L X)












## Photometric Data

### TOPIX INTERIOR




### TOPIX EXTERIOR




## Installation Options

### REMOTE DRIVER (With Controls D8)

**A:** 8″ x **B:** 2″-1/2 x **C:** 2″-1/2
**A:** 203mm x **B:** 64mm x **C:** 64mm


- For Remote application
- ETL Listed
- Damp rated





### REMOTE DRIVER (With Controls D1)

**A:** 8″ x **B:** 2″-3/16 x **C:** 4″-1/4
**A:** 203mm x **B:** 72mm x **C:** 108mm


- For Remote application
- ETL Listed
- Damp rated





### CF - CONCRETE BOX 153




### CL - CONCRETE BOX TR 154





### MK - MUD KIT 4




Requires 4" junction box

Used with
TOPIX INTERIOR only

### MK - MUD KIT 2




Requires 4" junction box

Used with
TOPIX EXTERIOR only

## Driver Options

### D1

- Dimming Control 0-10V
- Dimming Range 1-100%
- Dim to off yes at 0.7mA
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥87
- THD @ Full Load <20%
- Title 24 Compliant

**Dimmer Compatibility**

- Leviton IP710-DLZ
- Lutron DVTV-XX
- WattStopper ADF-120277
- Synergy Lighting Controls ISD BC

### D8

- Dimming Control Phase Control
- Dimming Range 10-100%
- Dim to off no
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥78
- THD @ Full Load <12%

**Dimmer Compatibility**

- Leviton IPE04-1LZ
- Lutron DVELV-300P

### ND

- Dimming Control NON DIMMABLE
- Power Factor @ Full Load >0.55
- Efficiency @ Full Load ≥72

**As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.**