



TOPIX



This multi award-winning luminaire ensures a playful light and gives you a lot of freedom. So you can put together an attractive or artistic cluster of light by combining multiple devices. You can also choose the color of the light: warm white or cool white. The fixture itself, which is semi recessed and semi surface, is available in aluminium grey or white.

Specification	CF	CL	MK
Installation Method:	Recessed	Recessed	4" junction box
Wall Thickness:	N/A	N/A	½" or ⅝" drywall
Adjustability:	Fixed		
Rating:	IP20		

Performance	
LED Maintenance:	L90>120,000h
McAdam Step:	3
CRI:	80
*SP:	2 x 1.1W

Delivered Lumens	3000K
Topix:	34Lm

Listing

ETL certified to US and Canadian safety standards.

Warranty

5-year limited warranty.

Ordering

ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: TPX-SP30FIO-A-MKRMTD1-UNV

Luminaire	Power	CCT	Function	Style	Finish	Installation	Application	Controls***
TPX TOPIX	SP Standard Power	30 3000K	FI Fixed, Interior Use	O Open	A Alu Grey W White	CF For concrete with flange CL For concrete without flange MK Mud kit into ½" or ⅝" drywall over 4" junction box	RMT Remote Power Supply	D1-UNV 0-10V dim 120-277V D1-347 0-10V dim 347V D8-120 FE ELV dim 120V

*** Contact factory Dali, DMX, or other dimming options.


Related Products

Topix L X (exterior)



Finish Options

TOPIX




ALU GREY



WHITE

Photometric Data

TOPIX




Installation Options

REMOTE DRIVER (With Controls D8)

A: 8" x B: 2"-1/2 x C: 2"-1/2
A: 203mm x B: 64mm x C: 64mm


- For Remote application
- ETL Listed
- Damp rated



REMOTE DRIVER (With Controls D1)

A: 8" x B: 2"-3/16 x C: 4"-1/4
A: 203mm x B: 72mm x C: 108mm




- For Remote application
- ETL Listed
- Damp rated



CF - CONCRETE BOX 153

CL - CONCRETE BOX TR 154

MK - MUD KIT 4



Requires 4" junction box



Driver Options

D1

- Dimming Control 0-10V
- Dimming Range 1-100%
- Dim to off yes at 0.7mA
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥ 87
- THD @ Full Load <20%
- Title 24 Compliant

Dimmer Compatibility

- Leviton IP710-DLZ
- Lutron DDTV-XX
- WattStopper ADF-120277
- Synergy Lighting Controls ISD BC

D8

- Dimming Control Phase Control
- Dimming Range 10-100%
- Dim to off no
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥ 78
- THD @ Full Load <12%

Dimmer Compatibility

- Leviton IPE04-1LZ
- Lutron DVELV-300P

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.