
DELTALIGHT




LOGIC W S 930

REFERENCE 304 33 811 930 B

AVAILABLE IN
ALU GREY 304 33 811 930 A
BLACK 304 33 811 930 B
FLEMISH BRONZE OUTDOOR 304 33 811 930 FBRX
ANTHRACITE 304 33 811 930 N
WHITE 304 33 811 930 W





View on website

General info	
LOCATION	indoor-outdoor
INSTALLATION	Wall Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - BOX
RECESSED DEPTH (MM)	115-140
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	0.7
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.LED POWER SUPPLY 350mA-DC INCL.1 x PG11

Electrical info	
ELECTRICAL	110-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	172lm // 7W // 26lm/W

Requirements

CONCRETE BOX 192
CONCRETE PACK LOGIC W S

For detailed installation instructions, please consult the manual : **304_33_811_XXX_HAND.pdf**


DELTALIGHT

LOGIC W S 930

304 33 811 930 B

FINISH YOUR SPECIFICATION

Concrete boxes




270 11 192 CONCRETE BOX 192

Cutout dimension (mm): 135 x 125

☐

Concrete packs



304 33 96 CONCRETE PACK LOGIC W S

Cutout dimension (mm): 135 x 125

☐

Notes: