




D-LINER 19 SBL LOC1 420 930 DIM5

32032 9305 B

AVAILABLE IN
BLACK 32032 9305 B



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
INGRESS PROTECTION	IP20
WEIGHT (KG)	0
ADJUSTABILITY	non adjustable
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY 260mA-DC INCL.1 x CABLE 5 x 0,75mm ² - 0,5m + WIELAND PLUG GST18i5 male pastelblue

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED flex 10W / CRI>90 (R9: 59) / 3000K / 1040lm
SDCM	SDCM3
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	1040lm // 10W // 123lm/W
LED TECHNICS (LUMINAIRE)	780lm // 11,5W // 68lm/W

For detailed installation instructions, please consult the manual : [32032_XXX5_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type

Mounting Kit



Acoustic climate-control ceiling Interlu SAPP

-

DELTALIGHT

D-LINER 19 SBL LOC1 420 930 DIM5

32032 9305 B



Acoustic climate-control ceiling Hunter Douglas 30BD

Notes: