

## ENTERO SQ-S TRIMLESS 92745



28525 9230 B

AVAILABLE IN

**BLACK** 28525 9230 B

**FULL WHITE** 28525 9230 FW

**GOLD COLOURED** 28525 9230 GC



[View on website](#)



### General info

|                               |  |
|-------------------------------|--|
| <b>LOCATION</b>               | indoor   |
| <b>INSTALLATION</b>           | Ceiling Recessed   |
| <b>CUTOUT SHAPE/SIZE (MM)</b> | rectangle - Ø KIT  |
| <b>RECESSED DEPTH (MM)</b>    | 110  |
| <b>INGRESS PROTECTION</b>     | IP20   |
| <b>WEIGHT (KG)</b>            | 0.24   |
| <b>ADJUSTABILITY</b>          | 0° to 30° swiveling, 355° rotatable  |
| <b>INFORMATION</b>            | REFLECTOR WFL-45°<br>EXCL.LED POWER SUPPLY 350-700mA-DC<br>Optional REFLECTORS 20° & 30° available |

### Electrical info

|                     |                           |
|---------------------|---------------------------|
| <b>CLASS</b>        | III                       |
| <b>DIM TYPE</b>     | depending on power supply |
| <b>ENERGY CLASS</b> | E                         |
| <b>CERTIFICATES</b> | CB, ENEC, EPD             |

### Lightsource info

|                                    |  |
|------------------------------------|--|
| <b>LIGHTSOURCE NAME</b>            | LED  |
| <b>LIGHTSOURCE</b>                 | LED array 5,8-12,4W / CRI>90 (R9: 60) / 2700K / 753-1403lm |
| <b>TM-30 VALUES</b>                | rf: 89 / Rg: 100   |
| <b>SDCM</b>                        | SDCM1  |
| <b>RISKGROUP</b>                   | RG1  |
| <b>LM80</b>                        | L90B10 > 50000   |
| <b>BEAMANGLE</b>                   | 45°  |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 1403lm // 12,4W // 113lm/W                                 |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 1086lm // 14,3W // 76lm/W                                  |

### Remarks

Max.500mA when using accessories

### Requirements

MOUNTING KIT ENTERO SQUARE S

LED POWER SUPPLY 350 / 500 / 700mA-DC DIM (Remote)

### Accessories

ENTERO S HONEYCOMB

ENTERO S LINEAR SPREAD LENS

ENTERO S SPREAD LENS

ENTERO S SOFTENING LENS

ENTERO S GLASS SBL



# DELTALIGHT

## ENTERO SQ-S TRIMLESS 92745

28525 9230 B


### LED power supplies

### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**300 48 350 ED1** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1

2

Dimtype: 1-10V

Cutout dimension (mm): 30




**300 48 350 ED5** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

2

Dimtype: DALI

Cutout dimension (mm): 45




**300 48 350 MDL** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL

2

Dimtype: non-dimmable

Cutout dimension (mm): 30




**300 48 350 WDL** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL

2

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45




**300 48 500 ED1** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1

2

Dimtype: 1-10V

Cutout dimension (mm): 30




**300 48 500 ED5** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

2

Dimtype: DALI

Cutout dimension (mm): 45




**300 48 500 MDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL

2

Dimtype: non-dimmable

Cutout dimension (mm): 30



**300 48 500 WDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL

2


Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45

# DELTALIGHT

## ENTERO SQ-S TRIMLESS 92745

28525 9230 B




**300 48 700 ED1** LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM1

2

Dimtype: 1-10V

Cutout dimension (mm): 30




**300 48 700 ED5** LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5

2

Dimtype: DALI

Cutout dimension (mm): 45




**300 48 700 MDL** LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W MDL

2

Dimtype: non-dimmable

Cutout dimension (mm): 30




**300 48 700 WDL** LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W WDL

2

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45




**300 90 61** LED POWER SUPPLY MULTI-POWER DIM6

2 | 2 | 2

Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56




**300 90 63** LED POWER SUPPLY MULTI-POWER DIM9

4(4) | 4(4) | 4(3)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82




**300 90 64** LED POWER SUPPLY MULTI-POWER DIM7

2(2) | 2(1) | 2(1)

Dimtype: 1-10V or push button


Cutout dimension (mm): 72



**300 90 67** LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9

2 | - | 2

Dimtype: 1-10V or DALI or push button




**300 90 68** LED POWER SUPPLY MULTI-POWER DIM5

2(2) | 2(1) | 2(1)

Dimtype: DALI

Cutout dimension (mm): 72



**300 90 69** LED POWER SUPPLY MULTI-POWER HV DIM9

2->6(6) | 6(4) | 4(3)


Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 84

# DELTALIGHT

## ENTERO SQ-S TRIMLESS 92745

28525 9230 B



**300 90 124** LED POWER SUPPLY MULTI-POWER DIM7

3(2) | 2(1) | 1(1)



**Dimtype: 1-10V or push button**

**Cutout dimension (mm): 55**




**300 90 125** LED POWER SUPPLY MULTI-POWER MINI DIM5

2(2) | 2(1) | 1(1)



**Dimtype: DALI**

**Cutout dimension (mm): 55**




**300 90 135** LED POWER SUPPLY MULTI-POWER HV

3->4 | 2->4 | 2->4



**Dimtype: non-dimmable**

**Cutout dimension (mm): 90**




**21012 0010** LED POWER SUPPLY MULTI POWER

2 | 2 | 2



**Dimtype: non-dimmable**

**Cutout dimension (mm): 50**




**21012 0021** LED POWER SUPPLY MULTI POWER DIM1

3 | 3 | 2



**Dimtype: 1-10V**

**Cutout dimension (mm): 54**




**21012 0035** LED POWER SUPPLY MULTI POWER DIM5

3 | 3 | 3



**Dimtype: DALI**

**Cutout dimension (mm): 54**




**21012 004W** LED POWER SUPPLY MULTI-POWER WDL

4(4) | 3(3) | 3(3)



**Dimtype: WDL = wireless dimmable**

**Cutout dimension (mm): 84**




**21012 005W** LED POWER SUPPLY MULTI-POWER COMPACT WDL

3 | 3 | 2



**Dimtype: WDL = wireless dimmable**

**Cutout dimension (mm): 54**




**21012 0268** LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8

2->2 | 0 | 0



**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 50**



**21012 0278** LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8

1 | 1




**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 55**

# DELTALIGHT

## ENTERO SQ-S TRIMLESS 92745

28525 9230 B




**21012 0288** LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8

2->3 | 2->2

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 55**




**21012 0298** LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

2 | 2 | 1

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 48**




**21012 0308** LED POWER SUPPLY 350mA / 7,35W DIM8

1

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 40**




**21012 0318** LED POWER SUPPLY 500mA / 10W DIM8

1

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 40**




**21012 0328** LED POWER SUPPLY 700mA / 15W DIM8

1

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 40**




**21012 0480** LED POWER SUPPLY 350mA-DC / 17W IP68

2(2)

**Dimtype: non-dimmable**

**Cutout dimension (mm): 60**




**21012 0490** LED POWER SUPPLY 700mA-DC / 30W IP68

2(1)

**Dimtype: non-dimmable**

**Cutout dimension (mm): 60**




**21012 0500** LED POWER SUPPLY 500mA-DC / 24W IP68

2(1)

**Dimtype: non-dimmable**

**Cutout dimension (mm): 60**




**21032 0295** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

2

**Dimtype: DALI**

**Cutout dimension (mm): 30**



**21032 0305** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

2


**Dimtype: DALI**

**Cutout dimension (mm): 30**

# DELTALIGHT

## ENTERO SQ-S TRIMLESS 92745

28525 9230 B



**21032 0315**

LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5


2



Dimtype: DALI

Cutout dimension (mm): 30

### Mounting kits




**28400 0040** MOUNTING KIT ENTERO SQ-S



Cutout dimension (mm): 106 x 106

### Mounting kits stretched ceiling




**28400 0100** MOUNTING KIT ENTERO SQ-S CSC



**28400 0160** MOUNTING KIT ENTERO SQ-S WSC




### Light altering devices



**28500 0010** ENTERO S LINEAR SPREAD LENS



**28500 0020** ENTERO S SPREAD LENS




**28500 0030** ENTERO S SOFTENING LENS




# DELTALIGHT

## ENTERO SQ-S TRIMLESS 92745


28525 9230 B



**28500 0040** ENTERO S GLASS SBL




**28500 0050 B** ENTERO S HONEYCOMB SINGLE USE B



**28500 0060 B** ENTERO S HONEYCOMB DOUBLE USE B

### Replaceable reflector / lens



**19810 0180** SPY 52 REFLECTOR 20°



**19810 0190** SPY 52 REFLECTOR 45°



**19810 0240** SPY 52 REFLECTOR 30°

Notes: