


27327 9300 FBR

Technical drawing of a mechanical part, likely a bracket or support. The drawing shows a side view of a component with a cylindrical feature. Dimensions are indicated: 160 (total length), 7 (thickness), 20 (width of a step), 11 (height of a base), 92 (length of the cylindrical part), and Ø39 (diameter of the cylindrical part). A circular feature is shown with a centerline and a dimension of 0.85° ± 5°.



Références optionnelles

1 / 3

TERMINEZ VOTRE SPÉCIFICATION


SMART 48

de luminaires



de luminaires indique combien d'appareils peuvent être raccordés (min -> max) à l'alimentation. Les valeurs avant et après le '|' correspondent respectivement au courant de pilotage minimal et maximal. Les valeurs entre parenthèses s'appliquent au 110V.


Courant min. | Courant max.



300 90 011 SMART 48 MODULATOR DIM9

19

Type de gradation: 1 à 10 V ou DALI ou bouton poussoir



300 90 012 SMART 48 MODULATOR WD

19

Type de gradation: WDL = dimmable sans fil


les alimentations led

de luminaires



de luminaires indique combien d'appareils peuvent être raccordés (min -> max) à l'alimentation. Les valeurs avant et après le '|' correspondent respectivement au courant de pilotage minimal et maximal. Les valeurs entre parenthèses s'appliquent au 110V.


Courant min. | Courant max.



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

10


Type de gradation: non dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

24

Type de gradation: non dimmable




21012 0230 LED POWER SUPPLY 48V-DC / 100W

10

Type de gradation: non dimmable

Dimension de découpe (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W

20

Type de gradation: non dimmable



Dimension de découpe (mm): 40

DELTALIGHT

SPL14 - SPY 39 FOCUS 930 MDL

27327 9300 FBR

COMPOSABLES COMPATIBLES

SPLITLINE 14 profile		Couleurs disponibles
	27300 0020 SPL14 - PROFILE 2m	
	27300 0030 SPL14 - PROFILE 3m	

Notes: