



INFORM SQ P585-9 DOWN 92767

25574 9220 B-B



AVAILABLE IN

BLACK-BLACK 25574 9220 B-B

BLACK-FLEMISH GOLD 25574 9220 B-FG

WHITE-BLACK 25574 9220 W-B

WHITE-WHITE 25574 9220 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	4.6
ADJUSTABILITY	non adjustable
INFORMATION	108 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 900/1350mA-DC INCL.4 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 2 x 0.75mm ²

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	3 x (LED cluster 10,5-16,7W / CRI>90 (R9: 50) / 2700K / 1519-2196lm)
TM-30 VALUES	Rf: 93 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	6588lm // 50,1W // 131lm/W
LED TECHNICS (LUMINAIRE)	5751lm // 57,6W // 100lm/W

Requirements

INFORM POWER SUPPLY 60W

INFORM SQ POWERBOX L 75W

Options

CABLE BASE R / S

COVERSET R 62-90-100 / S 62-80-90

CONNECTION ST / CONNECTION TRIMLESS

SUSPENSION ST / SUSPENSION TRIMLESS

DELTALIGHT


INFORM SQ P585-9 DOWN 92767

25574 9220 B-B

For detailed installation instructions, please consult the manual : [25574_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply



	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

LED power supplies

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.






Min current | Max current

	25510 0405 INFORM POWER SUPPLY 60W DIMS	1 ☐
	Dimtype: DALI	
	25510 0450 INFORM POWER SUPPLY 60W	1 ☐
	Dimtype: non-dimmable	

DELTALIGHT

INFORM SQ P585-9 DOWN 92767




25574 9220 B-B

Power box		# of Fixtures
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '!' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
	25510 0500 B INFORM SQ POWERBOX L 75W B	1 ☐
	Dimtype: non-dimmable	
	25510 0500 W INFORM SQ POWERBOX L 75W W	1 ☐
	25510 0515 B INFORM SQ POWERBOX L 75W DIM5 B	1 ☐
	Dimtype: DALI	
	25510 0515 W INFORM SQ POWERBOX L 75W DIM5 W	1 ☐
Coversets		
	204 00 62 ANO COVERSET R 62 ANO	☐
	204 00 62 B COVERSET R 62 B	☐
	204 00 62 W COVERSET R 62 W	☐
	204 00 90 ANO COVERSET R 90 ANO	☐
	204 00 90 B COVERSET R 90 B	☐
	204 00 90 W COVERSET R 90 W	☐
	204 00 100 ANO COVERSET R 100 ANO	☐



DELTALIGHT

INFORM SQ P585-9 DOWN 92767

25574 9220 B-B

	<u>204 00 100 B</u>	COVERSET R 100 B	☐
	<u>204 00 100 W</u>	COVERSET R 100 W	☐
	<u>204 62 62 ANO</u>	COVERSET S 62 ANO	☐
	<u>204 62 62 B</u>	COVERSET S 62 B	☐
	<u>204 62 62 W</u>	COVERSET S 62 W	☐
	<u>204 80 80 ANO</u>	COVERSET S 80 ANO	☐
	<u>204 80 80 B</u>	COVERSET S 80 B	☐
	<u>204 80 80 W</u>	COVERSET S 80 W	☐
	<u>204 90 90 ANO</u>	COVERSET S 90 ANO	☐
	<u>204 90 90 B</u>	COVERSET S 90 B	☐
	<u>204 90 90 W</u>	COVERSET S 90 W	☐

Suspension parts

	<u>328 10 01</u>	SUSPENSION TRIMLESS O.F.A.	☐
	Cutout dimension (mm): 62 (CONCRETE: 102)		
	<u>15225 0340 B</u>	SUSPENSION ST B	☐
	Cutout dimension (mm): 27		


DELTA LIGHT

INFORM SQ P585-9 DOWN 92767

25574 9220 B-B

15225 0340 W SUSPENSION ST W

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0360 B CONNECTION ST B

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

Notes: