
DELTALIGHT




PARTOU FLAT OK 93036 S1

REFERENCE 25220 9320 B

AVAILABLE IN
BLACK 25220 9320 B
FLEMISH BRONZE 25220 9320 FBR
FLEMISH GOLD 25220 9320 FG
WHITE 25220 9320 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 76
RECESSED DEPTH (MM)	55
THICKNESS OF MOUNTING SURFACE (MM)	min.5
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 20° swiveling
INFORMATION	LENS FL-36° EXCL.LED POWER SUPPLY 350mA-DC

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	36°
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	519lm // 6,7W // 78lm/W

Requirements

LED POWER SUPPLY 350mA-DC DIM

Options

PLASTERKIT 101

For detailed installation instructions, please consult the manual : **25220_XXX0_HAND.pdf**

DELTALIGHT

PARTOU FLAT OK 93036 S1


25220 9320 B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 **System ceiling**	-	
 **Plasterboard**	-	
 **Stucanet**	202 11 19 - PLASTERKIT 101	Required
 **Wood**	-	
 **Concrete + plaster**	202 11 19 - PLASTERKIT 101	Required
 **Lintel + plaster**	202 11 19 - PLASTERKIT 101	Required
 **Hollow-core slab + plaster**	202 11 19 - PLASTERKIT 101	Required
 **Stretched ceiling**	-	

FINISH YOUR SPECIFICATION

Emergency units



21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B

Cutout dimension (mm): 27

21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

LED power supplies

of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


of Fixtures

Min current | Max current

DELTALIGHT

PARTOU FLAT OK 93036 S1


25220 9320 B



300 90 91 LED POWER SUPPLY 350mA-DC / 15W — 2(1)

Dimtype: non-dimmable


Cutout dimension (mm): 40



300 90 108 U LED POWER SUPPLY 350mA-DC / 8W — 1

Dimtype: non-dimmable


Cutout dimension (mm): 47



300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 — 3(2)

Dimtype: 1-10V or push button


Cutout dimension (mm): 55



300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 — 2(2)

Dimtype: DALI


Cutout dimension (mm): 55



21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8 — 1

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 50



21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 — 2->2

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 50




21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 — 2(2)

Dimtype: non-dimmable

Cutout dimension (mm): 60

Plasterkits



202 11 19 PLASTERKIT 101

Cutout dimension (mm): 80 x 180

Notes:

PARTOU FLAT OK 93036 S1

25220 9320 B