DELTALIGHT

iMAX II ROUND ADJUSTABLE TRIMLESS CL 9306

REFERENCE 24224 9310-R





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - Ø KIT
RECESSED DEPTH (MM)	145
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable
INFORMATION	LENS SP-6° EXCL.LED POWER SUPPLY 700-1050mA-DC

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 2-3,2W / CRI>90 / 3000K / 229-319lm
SDCM	SDCM3
RISKGROUP	RG2 (threshold 0,6m)
BEAMANGLE	6°
LED TECHNICS (LIGHT SOURCE)	319lm // 3,2W // 100lm/W
LED TECHNICS (LUMINAIRE)	286lm // 3,7W // 78lm/W

Requirements

LED POWER SUPPLY 700 / 1050mA-DC DIM (Remote)
MOUNTING KIT R102 TRIMLESS O.F.A.
iMAX II TUBE TRIMLESS

Accessories

IMAX HONEYCOMB

For detailed installation instructions, please consult the manual : **24224_XXX0-R_HAND.pdf**

iMAX II ROUND ADJUSTABLE TRIMLESS CL 9306

24224 9310-R

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
System ceiling	15212 2010 - MOUNTING KIT R102 TRIMLESS O.F.A.	Required
Plasterboard	15212 2010 - MOUNTING KIT R102 TRIMLESS O.F.A.	Required
Concrete + plaster	15212 2010 - MOUNTING KIT R102 TRIMLESS O.F.A.	Required
Lintel + plaster	15212 2010 - MOUNTING KIT R102 TRIMLESS O.F.A.	Required
Hollow-core slab + plaster	15212 2010 - MOUNTING KIT R102 TRIMLESS O.F.A.	Required
Stretched ceiling	15212 0170 - MOUNTING KIT R102 TRIMLESS WSC	Required
	15212 0090 - MOUNTING KIT R102 TRIMLESS CSC	Required

FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 48 700 ED1 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM1 2->13

Dimtype: 1-10V

Cutout dimension (mm): 30



300 48 700 ED5 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5 2->13

Dimtype: DALI

Cutout dimension (mm): 45



300 48 700 MDL LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W MDL 2->13

Dimtype: non-dimmable

Cutout dimension (mm): 30



300 48 700 PRO ED1 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W PRO DIM1 2->13

Dimtype: 1-10V

Cutout dimension (mm): 30

iMAX II ROUND ADJUSTABLE TRIMLESS CL 9306

24224 9310-R



300 48 700 PRO ED5 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W PRO DIM5 2->13

Dimtype: DALI

Cutout dimension (mm): 45



300 48 700 PRO WDL LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W PRO WDL 2->13

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45



300 48 700 WDL LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W WDL 2->13

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45



300 90 61 LED POWER SUPPLY MULTI-POWER DIM6 15 | - | -

Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56



300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 15(6) | - | -

Dimtype: 1-10V or push button

Cutout dimension (mm): 72



300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 3->14 | 3->14 | -

Dimtype: 1-10V or DALI or push button



300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 2->15(7) | -

Dimtype: DALI

Cutout dimension (mm): 72



300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 29(19) | -

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 84



300 90 93 LED POWER SUPPLY 700mA-DC / 17W 2->8(5)

Dimtype: non-dimmable

Cutout dimension (mm): 48



300 90 118 LED POWER SUPPLY 700mA-DC / 20W DIM8 6->9

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55

iMAX II ROUND ADJUSTABLE TRIMLESS CL 9306

24224 9310-R



300 90 123 LED POWER SUPPLY 700mA-DC / 36W DIM8 2->17

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 50



300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 2->10(7) | -

Dimtype: 1-10V or push button

Cutout dimension (mm): 55



300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 2->9(7) | -

Dimtype: DALI

Cutout dimension (mm): 55



300 90 134 LED POWER SUPPLY MULTI-POWER HV DIM7 28(18) | - | -

Dimtype: 1-10V or push button

Cutout dimension (mm): 84



300 90 135 LED POWER SUPPLY MULTI-POWER HV 10->28 | 9->20 | -

Dimtype: non-dimmable

Cutout dimension (mm): 90



300 90 136 LED POWER SUPPLY MULTI-POWER HC DIM9 - | 14(12)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 90



300 90 148 LED POWER SUPPLY 1050mA-DC / 22W 7(3)

Dimtype: non-dimmable

Cutout dimension (mm): 48



21012 004W LED POWER SUPPLY MULTI-POWER WDL 23(18) | 17(11) | -

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 84



21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL 4->17 | 4->12 | -

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 54



21012 0490 LED POWER SUPPLY 700mA-DC / 30W IP68 2->14(7)

Dimtype: non-dimmable

Cutout dimension (mm): 60

iMAX II ROUND ADJUSTABLE TRIMLESS CL 9306

24224 9310-R



21032 0315 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5 2->14

Dimtype: DALI

Cutout dimension (mm): 30



21032 0385 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W PRO DIM5 2->14

Dimtype: DALI

Cutout dimension (mm): 30

Mounting kits



15212 2010 MOUNTING KIT R102 TRIMLESS O.F.A.

Cutout dimension (mm): 127

Mounting kits stretched ceiling



15212 0090 MOUNTING KIT R102 TRIMLESS CSC



15212 0170 MOUNTING KIT R102 TRIMLESS WSC

Light altering devices



400 03 01 B iMAX HONEYCOMB B

Finish your product



24213 0020 B iMAX II TUBE ROUND TRIMLESS B

iMAX II ROUND ADJUSTABLE TRIMLESS CL 9306

24224 9310-R

24213 0020 FG	iMAX II TUBE ROUND TRIMLESS FG	☐
24213 0020 MMAT	iMAX II TUBE ROUND TRIMLESS MMAT	☐
24213 0020 W	iMAX II TUBE ROUND TRIMLESS W	☐

Notes: