DELTALIGHT



OML50 C - LED ARRAY UP TW 984mm 950 DIM5

REFERENCE 31144 9005

View on website

General info	
LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.9
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	@ 2700K: LED cluster 11,2W / CRI>90 (R9: 50) / 2700K-5000K / 1464lm Or @ 5000K: LED cluster 10,1W / CRI>90 (R9: 50) / 2700K-5000K / 1752lm
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	@ 2700K: 1464lm // 11,2W // 131lm/W Or @ 5000K: 1752lm // 10,1W // 173lm/W

Options

WIRELESS CONTROL DIM5

Notes: