



SPY 52 ON 92720

19823 9220 W

AVAILABLE IN

NOIR 19823 9220 B


FLEMISH BRONZE 19823 9220 FBR

FLEMISH GOLD 19823 9220 FG

ENTIÈREMENT BLANC 19823 9220 FW

COULEUR OR 19823 9220 GC

BLANC 19823 9220 W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Applique
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° à 90° inclinable, 355° rotatif
INFORMATION	REFLECTOR FL-20° EXCL.LED POWER SUPPLY 350-700mA-DC Optional REFLECTORS 30° & 45° available

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	E
CERTIFICATION	CB, ENEC, LCA

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-12,4W / CRI>90 (R9: 60) / 2700K / 753-1403lm
RVALUES	rf: 89 / Rg: 100
SDMC	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	1403lm // 12,4W // 113lm/W
LED TECHNICS (LUMINAIRE)	879lm // 14,3W // 62lm/W

Requirements

SPY 52 TUBE

LED POWER SUPPLY 350 / 500 / 700mA-DC DIM

Options

COVERSET R 90-100

Accessories

HONEYCOMB 42

SPREAD LENS 42








LINEAR SPREAD LENS 42

SOFTENING LENS 42

GLASS SBL 42







For detailed installation instructions, please consult the manual : [19823_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

les alimentations led			# of Fixtures
 web2print_power_supply_info_box			Min current Max current
	300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1 Dimtype: 1 à 10 V Cutout dimension (mm): 30	2	☐
	300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 Dimtype: DALI Cutout dimension (mm): 45	2	☐
	300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL Dimtype: non dimmable Cutout dimension (mm): 30	2	☐
	300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 45	2	☐
	300 48 500 ED1 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1 Dimtype: 1 à 10 V Cutout dimension (mm): 30	2	☐
	300 48 500 ED5 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 Dimtype: DALI Cutout dimension (mm): 45	2	☐
	300 48 500 MDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL Dimtype: non dimmable Cutout dimension (mm): 30	2	☐








SPY 52 ON 92720

19823 9220 W

	<u>300 48 500 WDL</u> LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL	2	☐
Dimtype: WDL = dimmable sans fil			
Cutout dimension (mm): 45			
	<u>300 48 700 ED1</u> LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM1	2	☐
Dimtype: 1 à 10 V			
Cutout dimension (mm): 30			
	<u>300 48 700 ED5</u> LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5	2	☐
Dimtype: DALI			
Cutout dimension (mm): 45			
	<u>300 48 700 MDL</u> LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W MDL	2	☐
Dimtype: non dimmable			
Cutout dimension (mm): 30			
	<u>300 48 700 WDL</u> LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W WDL	2	☐
Dimtype: WDL = dimmable sans fil			
Cutout dimension (mm): 45			
	<u>300 90 61</u> LED POWER SUPPLY MULTI-POWER DIM6	2 2 2	☐
Dimtype: fin de phase ou bouton poussoir			
Cutout dimension (mm): 56			
	<u>300 90 63</u> LED POWER SUPPLY MULTI-POWER DIM9	4(4) 4(4) 4(3)	☐
Dimtype: 1 à 10 V ou DALI ou bouton poussoir			
Cutout dimension (mm): 82			
	<u>300 90 64</u> LED POWER SUPPLY MULTI-POWER DIM7	2(2) 2(1) 2(1)	☐
Dimtype: 1 à 10 V ou bouton poussoir			
Cutout dimension (mm): 72			
	<u>300 90 67</u> LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9	2 - 2	☐
Dimtype: 1 à 10 V ou DALI ou bouton poussoir			
	<u>300 90 68</u> LED POWER SUPPLY MULTI-POWER DIM5	2(2) 2(1) 2(1)	☐
Dimtype: DALI			
Cutout dimension (mm): 72			

SPY 52 ON 92720

19823 9220 W

	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 Dimtype: 1 à 10 V ou DALI ou bouton poussoir Cutout dimension (mm): 84	2->6(6) 6(4) 4(3)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1 à 10 V ou bouton poussoir Cutout dimension (mm): 55	3(2) 2(1) 1(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 Dimtype: DALI Cutout dimension (mm): 55	2(2) 2(1) 1(1)	☐
	300 90 135 LED POWER SUPPLY MULTI-POWER HV Dimtype: non dimmable Cutout dimension (mm): 90	3->4 2->4 2->4	☐
	21012 0010 LED POWER SUPPLY MULTI POWER Dimtype: non dimmable Cutout dimension (mm): 50	2 2 2	☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1 Dimtype: 1 à 10 V Cutout dimension (mm): 54	3 3 2	☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5 Dimtype: DALI Cutout dimension (mm): 54	3 3 3	☐
	21012 004W LED POWER SUPPLY MULTI-POWER WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 84	4(4) 3(3) 3(3)	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 54	3 3 2	☐
	21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 Dimtype: fin de phase Cutout dimension (mm): 50	2->2 0 0	☐

SPY 52 ON 92720

19823 9220 W

	21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8 Dimtype: fin de phase Cutout dimension (mm): 55	1 1	☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 Dimtype: fin de phase Cutout dimension (mm): 55	2->3 2->2	☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 Dimtype: fin de phase Cutout dimension (mm): 48	2 2 1	☐
	21012 0308 LED POWER SUPPLY 350mA / 7,35W DIM8 Dimtype: fin de phase Cutout dimension (mm): 40	1	☐
	21012 0318 LED POWER SUPPLY 500mA / 10W DIM8 Dimtype: fin de phase Cutout dimension (mm): 40	1	☐
	21012 0328 LED POWER SUPPLY 700mA / 15W DIM8 Dimtype: fin de phase Cutout dimension (mm): 40	1	☐
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 Dimtype: non dimmable Cutout dimension (mm): 60	2(2)	☐
	21012 0490 LED POWER SUPPLY 700mA-DC / 30W IP68 Dimtype: non dimmable Cutout dimension (mm): 60	2(1)	☐
	21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68 Dimtype: non dimmable Cutout dimension (mm): 60	2(1)	☐
	21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 Dimtype: DALI Cutout dimension (mm): 30	2	☐


DELTALIGHT

SPY 52 ON 92720



19823 9220 W

	21032 0305	LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	2	☐
	Dimtype: DALI			
	Cutout dimension (mm): 30			
	21032 0315	LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5	2	☐
	Dimtype: DALI			
	Cutout dimension (mm): 30			

les sets pour recouvrement plafond

	204 00 90 ANO	COVERSET R 90 ANO		☐
	204 00 90 B	COVERSET R 90 B		☐
	204 00 90 W	COVERSET R 90 W		☐
	204 00 100 ANO	COVERSET R 100 ANO		☐
	204 00 100 B	COVERSET R 100 B		☐
	204 00 100 W	COVERSET R 100 W		☐

modifier les dispositifs de lumière

	19810 0010 B	HONEYCOMB 42 SINGLE USE B		☐
	19810 0020	LINEAR SPREAD LENS 42		☐


DELTALIGHT

SPY 52 ON 92720

19823 9220 W

	19810 0030	SPREAD LENS 42	☐
	19810 0040	SOFTENING LENS 42	☐
	19810 0050	GLASS SBL 42	☐
	19810 0060 B	HONEYCOMB 42 DOUBLE USE B	☐

Terminez votre produit

	19810 0100 B	SPY 52 TUBE B	☐
	19810 0100 FBR	SPY 52 TUBE FBR	☐
	19810 0100 FG	SPY 52 TUBE FG	☐
	19810 0100 GC	SPY 52 TUBE GC	☐
	19810 0100 W	SPY 52 TUBE W	☐

Réflecteur / lentille remplaçable

	19810 0180	SPY 52 REFLECTOR 20°	☐
--	-------------------	----------------------	--------------------------

DELTALIGHT

SPY 52 ON 92720

19823 9220 W



19810 0190 SPY 52 REFLECTOR 45°

☐

19810 0240 SPY 52 REFLECTOR 30°

☐

Notes: