
DELTALIGHT




HEDRA ON 2 92733 DIM1

REFERENCE 473 231 812 922 ED1 BBR-B

AVAILABLE IN
BLACK-BLACK 473 231 812 922 ED1 B-B
BLACK BRONZE-BLACK 473 231 812 922 ED1 BBR-B
GOLD COLORED-BLACK 473 231 812 922 ED1 GC-B
WHITE-WHITE 473 231 812 922 ED1 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Wall Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.9
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	2 x REFLECTOR FL-33° INCL.DIMMABLE LED POWER SUPPLY 350mA-DC

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	1-10V
ENERGY CLASS	D
CERTIFICATES	CB, EAC, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm)
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	33°
LED TECHNICS (LIGHT SOURCE)	1506lm // 11,6W // 129lm/W
LED TECHNICS (LUMINAIRE)	756lm // 13,3W // 57lm/W

Requirements

VIZIR TUBE

Accessories

VIZIR HONEYCOMB
VIZIR SOFTENING LENS

For detailed installation instructions, please consult the manual : **473_231_812_XXX_ED1_HAND.pdf**


DELTALIGHT

HEDRA ON 2 92733 DIM1

473 231 812 922 ED1 BBR-B

FINISH YOUR SPECIFICATION

Miscellaneous control equipment




300 90 016 ED1 WIRELESS CONTROL 5A DIM1 ☐


Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 86

Light altering devices




473 03 01 B VIZIR HONEYCOMB B ☐



473 03 04 VIZIR SOFTENING LENS ☐

Finish your product



473 01 00 B VIZIR TUBE B ☐

473 01 00 FBR VIZIR TUBE FBR ☐

473 01 00 FG VIZIR TUBE FG ☐

473 01 00 W VIZIR TUBE W ☐

Notes: