



OML50 - PRISMATIC LENS DU HE 2624mm 940 DIM5

31645 9405 B

BESCHIKBAAR IN
ZWART 31645 9405 B



[Bekijk op website](#)



Algemene info

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	3.5
INFO	INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT

Elektrische info

ELEKTRISCH	220-240V / 0 50-60Hz
KLASSE	I
VOEDING INBEGREPEN	YES
DIM TYPE	DALI
ENERGIE KLASSE	D
CERTIFICATES	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 39W / CRI>90 (R9: 50) / 4000K / 6653lm UP: LED cluster 32,6W / CRI>90 (R9: 50) / 4000K / 5286lm
TM-30 WAARDEN	Rf: 90 / Rg: 101
SMDC	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	DOWN: 6653lm // 39W // 171lm/W UP: 5286lm // 32,6W // 162lm/W

Opties

WIRELESS CONTROL DIM5

Notes: