





LASS-OH! L210-4 93034

24818 9320 GC

AVAILABLE IN
BLACK 24818 9320 B
GOLD COLOURED 24818 9320 GC



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.9
ADJUSTABILITY	non adjustable
INFORMATION	INCL.4 x DOT.COM S6 modules per module: 6 x REFLECTOR FL-34° EXCL.LED POWER SUPPLY 700mA-DC INCL.2 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 2 x 0.75mm ²

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	4 x (LED cluster 6,1W / CRI>90 (R9: 50) / 3000K / 683lm)
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
LM80	L80 > 60000
BEAMANGLE	34°
LED TECHNICS (LIGHT SOURCE)	2732lm // 24,4W // 112lm/W
LED TECHNICS (LUMINAIRE)	2159lm // 28,1W // 77lm/W

Requirements	
LASS-OH! POWERBOX	
LED POWER SUPPLY 700mA-DC DIM	

Options	
CABLE BASE R / S	
COVERSET R 62-90-100 / S 62-80-90	
CONNECTION ST / CONNECTION TRIMLESS	
SUSPENSION ST / SUSPENSION TRIMLESS	

Accessories	
JIHA S / R	

For detailed installation instructions, please consult the manual : [24818_XXXX_HAND.pdf](#)



FINISH YOUR SPECIFICATION

Current supply

	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

LED power supplies


of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
	21012 0010 LED POWER SUPPLY MULTI POWER Dimtype: non-dimmable Cutout dimension (mm): 50	1 ☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1 Dimtype: 1-10V Cutout dimension (mm): 54	1 ☐


DELTALIGHT


LASS-OH! L210-4 93034


24818 9320 GC



	21012 0035 LED POWER SUPPLY MULTI POWER DIM5	1	☐
Dimtype: DALI			
Cutout dimension (mm): 54			

Power box	# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.	Min current Max current

	24814 0010 B LASS-OH! POWERBOX B	1	☐
Dimtype: non-dimmable			

	24814 0011 B LASS-OH! POWERBOX DIM1 B	1	☐
Dimtype: 1-10V			

	24814 0015 B LASS-OH! POWERBOX DIM5 B	1	☐
Dimtype: DALI			

Coversets		
	204 00 62 ANO COVERSET R 62 ANO	☐
	204 00 62 B COVERSET R 62 B	☐
	204 00 62 W COVERSET R 62 W	☐
	204 00 90 ANO COVERSET R 90 ANO	☐
	204 00 90 B COVERSET R 90 B	☐

DELTALIGHT

LASS-OH! L210-4 93034

24818 9320 GC

	<u>204 00 90 W</u>	COVERSET R 90 W	☐
	<u>204 00 100 ANO</u>	COVERSET R 100 ANO	☐
	<u>204 00 100 B</u>	COVERSET R 100 B	☐
	<u>204 00 100 W</u>	COVERSET R 100 W	☐
	<u>204 62 62 ANO</u>	COVERSET S 62 ANO	☐
	<u>204 62 62 B</u>	COVERSET S 62 B	☐
	<u>204 62 62 W</u>	COVERSET S 62 W	☐
	<u>204 80 80 ANO</u>	COVERSET S 80 ANO	☐
	<u>204 80 80 B</u>	COVERSET S 80 B	☐
	<u>204 80 80 W</u>	COVERSET S 80 W	☐
	<u>204 90 90 ANO</u>	COVERSET S 90 ANO	☐
	<u>204 90 90 B</u>	COVERSET S 90 B	☐
	<u>204 90 90 W</u>	COVERSET S 90 W	☐

DELTALIGHT

LASS-OH! L210-4 93034

24818 9320 GC



Suspension parts

	328 10 01 SUSPENSION TRIMLESS O.F.A.	☐
Cutout dimension (mm): 62 (CONCRETE: 102)		
	15225 0340 B SUSPENSION ST B	☐
Cutout dimension (mm): 27		
	15225 0340 W SUSPENSION ST W	☐

Electric connection parts

	328 10 03 CONNECTION TRIMLESS O.F.A.	☐
Cutout dimension (mm): 62 (CONCRETE: 102)		
	15225 0360 B CONNECTION ST B	☐
Cutout dimension (mm): 43		
	15225 0360 W CONNECTION ST W	☐

Light altering devices

	24814 0020 B JIHA! S B	☐
	24814 0030 B JIHA! R B	☐

DELTALIGHT

LASS-OH! L210-4 93034

24818 9320 GC

Notes: