
DELTALIGHT




OONO ON 2 927

REFERENCE 29614 9200 B

AVAILABLE IN
BLACK 29614 9200 B
GOLD COLOURED 29614 9200 GC
WHITE 29614 9200 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Wall Surface mounted
INGRESS PROTECTION	IP44/20
PROTECTION AGAINST MECHANICAL IMPACT	IK04
WEIGHT (KG)	2.1
ADJUSTABILITY	non adjustable
INFORMATION	INCL.LED POWER SUPPLY 500mA-DC

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm)
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	2082lm // 17,2W // 121lm/W
LED TECHNICS (LUMINAIRE)	902lm // 19,8W // 46lm/W

Remarks

IP44 : wall mounted / IP20 : ceiling mounted

For detailed installation instructions, please consult the manual : **29614_XXX0_HAND.pdf**

DELTALIGHT

OONO ON 2 927

29614 9200 B

Notes: