

DELTALIGHT



INFORM SQ P475-9 DOWN 92767

25572 9220 B-FG



AVAILABLE IN

BLACK-BLACK 25572 9220 B-B

BLACK-FLEMISH GOLD 25572 9220 B-FG

WHITE-BLACK 25572 9220 W-B

WHITE-WHITE 25572 9220 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.9
ADJUSTABILITY	non adjustable
INFORMATION	108 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 900/1350mA-DC INCL.4 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 2 x 0.75mm ²

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	3 x (LED cluster 10,5-16,7W / CRI>90 (R9: 50) / 2700K / 1519-2196lm)
TM-30 VALUES	Rf: 93 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	6588lm // 50,1W // 131lm/W
LED TECHNICS (LUMINAIRE)	5751lm // 57,6W // 100lm/W

Requirements

INFORM POWER SUPPLY 60W

INFORM SQ POWERBOX L 75W

Options

CABLE BASE R / S

COVERSET R 62-90-100 / S 62-80-90

CONNECTION ST / CONNECTION TRIMLESS

SUSPENSION ST / SUSPENSION TRIMLESS

For detailed installation instructions, please consult the manual : [25572_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply



	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

LED power supplies

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

	25510 0405 INFORM POWER SUPPLY 60W DIMS	1 ☐
	Dimtype: DALI	
	25510 0450 INFORM POWER SUPPLY 60W	1 ☐
	Dimtype: non-dimmable	


DELTALIGHT

INFORM SQ P475-9 DOWN 92767

25572 9220 B-FG

	<u>204 00 100 B</u>	COVERSET R 100 B	☐
	<u>204 00 100 W</u>	COVERSET R 100 W	☐
	<u>204 62 62 ANO</u>	COVERSET S 62 ANO	☐
	<u>204 62 62 B</u>	COVERSET S 62 B	☐
	<u>204 62 62 W</u>	COVERSET S 62 W	☐
	<u>204 80 80 ANO</u>	COVERSET S 80 ANO	☐
	<u>204 80 80 B</u>	COVERSET S 80 B	☐
	<u>204 80 80 W</u>	COVERSET S 80 W	☐
	<u>204 90 90 ANO</u>	COVERSET S 90 ANO	☐
	<u>204 90 90 B</u>	COVERSET S 90 B	☐
	<u>204 90 90 W</u>	COVERSET S 90 W	☐

Suspension parts

	<u>328 10 01</u>	SUSPENSION TRIMLESS O.F.A.	☐
	Cutout dimension (mm): 62 (CONCRETE: 102)		
	<u>15225 0340 B</u>	SUSPENSION ST B	☐
	Cutout dimension (mm): 27		

DELTALIGHT

INFORM SQ P475-9 DOWN 92767


25572 9220 B-FG

15225 0340 W

SUSPENSION ST W

☐

Electric connection parts



328 10 03

CONNECTION TRIMLESS O.F.A.

☐

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0360 B

CONNECTION ST B

☐

Cutout dimension (mm): 43

15225 0360 W

CONNECTION ST W

☐

Notes: