
DELTALIGHT




INFORM SQ P585-9 DOWN 92767

REFERENCE 25574 9220 W-B

AVAILABLE IN
BLACK-BLACK 25574 9220 B-B
BLACK-FLEMISH GOLD 25574 9220 B-FG
WHITE-BLACK 25574 9220 W-B
WHITE-WHITE 25574 9220 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	4.6
ADJUSTABILITY	non adjustable
INFORMATION	108 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 900/1350mA-DC INCL.4 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 2 x 0.75mm²

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	3 x (LED cluster 10,5-16,7W / CRI>90 (R9: 50) / 2700K / 1519-2196lm)
TM-30 VALUES	Rf: 93 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	6588lm // 50,1W // 131lm/W
LED TECHNICS (LUMINAIRE)	5751lm // 57,6W // 100lm/W

Requirements

INFORM POWER SUPPLY 60W
INFORM SQ POWERBOX L 75W

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS

DELTALIGHT


INFORM SQ P585-9 DOWN 92767

25574 9220 W-B

For detailed installation instructions, please consult the manual : **25574_XXX0_HAND.pdf**

FINISH YOUR SPECIFICATION


Current supply



203 99 55 ANO CABLE BASE R ANO ☐

203 99 55 B CABLE BASE R B ☐

203 99 55 W CABLE BASE R W ☐



203 99 56 ANO CABLE BASE S ANO ☐

203 99 56 B CABLE BASE S B ☐


203 99 56 W CABLE BASE S W ☐

LED power supplies

of Fixtures


ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



25510 0405 INFORM POWER SUPPLY 60W DIM5 1 ☐

Dimtype: DALI



25510 0450 INFORM POWER SUPPLY 60W 1 ☐

Dimtype: non-dimmable

DELTALIGHT

INFORM SQ P585-9 DOWN 92767


25574 9220 W-B

Power box

of Fixtures

of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



25510 0500 B INFORM SQ POWERBOX L 75W B — 1

Dimtype: non-dimmable

25510 0500 W INFORM SQ POWERBOX L 75W W — 1




25510 0515 B INFORM SQ POWERBOX L 75W DIM5 B — 1

Dimtype: DALI

25510 0515 W INFORM SQ POWERBOX L 75W DIM5 W — 1


Coversets



204 00 62 ANO COVERSET R 62 ANO

204 00 62 B COVERSET R 62 B


204 00 62 W COVERSET R 62 W



204 00 90 ANO COVERSET R 90 ANO

204 00 90 B COVERSET R 90 B




204 00 90 W COVERSET R 90 W




204 00 100 ANO COVERSET R 100 ANO

INFORM SQ P585-9 DOWN 92767


25574 9220 W-B

	204 00 100 B	COVERSET R 100 B
	204 00 100 W	COVERSET R 100 W
	**204 62 62 ANO**	COVERSET S 62 ANO
	204 62 62 B	COVERSET S 62 B
	204 62 62 W	COVERSET S 62 W
	**204 80 80 ANO**	COVERSET S 80 ANO
	204 80 80 B	COVERSET S 80 B
	204 80 80 W	COVERSET S 80 W
	**204 90 90 ANO**	COVERSET S 90 ANO
	204 90 90 B	COVERSET S 90 B
	204 90 90 W	COVERSET S 90 W

Suspension parts

	**328 10 01**	SUSPENSION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)

	**15225 0340 B**	SUSPENSION ST B


Cutout dimension (mm): 27

INFORM SQ P585-9 DOWN 92767

25574 9220 W-B

15225 0340 W SUSPENSION ST W

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0360 B CONNECTION ST B

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

Notes: