
DELTALIGHT



DEEP RINGO DYNAMIC FOCUS TRIMLESS 930

REFERENCE 32112 9300 CR

AVAILABLE IN
BLACK 32112 9300 B
BRUSHED ALU 32112 9300 BRA
BRUSHED ANTHRACITE 32112 9300 BRAT
BRUSHED BROWN BRONZE 32112 9300 BRBB
BRUSHED COPPER 32112 9300 BRCU
BRUSHED GOLD 32112 9300 BRG
BRUSHED OLD BRONZE 32112 9300 BROB
CREAM 32112 9300 CR
PIANO BLACK 32112 9300 PB
WHITE 32112 9300 W



View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - Ø KIT
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	non adjustable

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	G

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	13° (central part only): LED array 5,8W / CRI>90 (R9: 55) / 3000K / 528lm Or 24° central part: LED array 1W / CRI>90 (R9: 55) / 3000K / 63lm 24° ring part: LED cluster 5,5W / CRI>90 (R9: 50) / 3000K / 914lm
SDCM	SDCM2 SDCM3
RISKGROUP	RG2 (threshold 0,6m) RG1
LM80	L90B10 > 41000 L80 > 60000
BEAMANGLE	13°-24°
LED TECHNICS (LIGHT SOURCE)	13° (central part only): 528lm // 5,8W // 94lm/W Or 24° central part: 63lm // 1W // 100lm/W 24° ring part: 914lm // 5,5W // 167lm/W
LED TECHNICS (LUMINAIRE)	13° (central part only): 475lm // 7W // 71lm/W Or 24° ring part: 366lm // 6W // 58lm/W

Requirements

MOUNTING KIT R82 TRIMLESS O.F.A.
LED POWER SUPPLY DYNAMIC FOCUS

DELTALIGHT

DEEP RINGO DYNAMIC FOCUS TRIMLESS 930

32112 9300 CR

For detailed installation instructions, please consult the manual : **32112_XXX0_HAND.pdf**

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 **System ceiling**	15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 **Plasterboard**	15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 **Stucanet**	15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 **Concrete + plaster**	15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 **Lintel + plaster**	15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 **Hollow-core slab + plaster**	15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 **Ventilation in plasterboard**	29810 0100 - MOUNTING KIT SIDE AIR ONLY 1	Required
	29810 0050 - MOUNTING KIT NO AIR 101	Required
	29810 0010 - MOUNTING KIT SIDE AIR 101	Required
 **Ventilation in concrete + plaster**	29810 0210 - MOUNTING KIT TOP AIR 101	Required
	29810 0050 - MOUNTING KIT NO AIR 101	Required
	29810 0200 - MOUNTING KIT TOP AIR ONLY 1	Required
 **Cold stretched ceiling**	15212 0070 - MOUNTING KIT R82 TRIMLESS CSC	Required
 **Warm stretched ceiling**	15212 0150 - MOUNTING KIT R82 TRIMLESS WSC	Required

FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

DELTALIGHT

DEEP RINGO DYNAMIC FOCUS TRIMLESS 930


32112 9300 CR



32110 0015 LED POWER SUPPLY DYNAMIC FOCUS DIM5 — 3

Dimtype: DALI

Cutout dimension (mm): 75




32110 0020 LED POWER SUPPLY DYNAMIC FOCUS + WIRELESS CONTROL DIM5 — 3

Dimtype: DALI

Cutout dimension (mm): 75


Mounting kits



15212 2000 MOUNTING KIT R82 TRIMLESS O.F.A.

Cutout dimension (mm): 105

Mounting kits stretched ceiling



15212 0070 MOUNTING KIT R82 TRIMLESS CSC



15212 0150 MOUNTING KIT R82 TRIMLESS WSC

Notes: