



OML50 - PRISMATIC LENS DU TW 984mm 950 DIM5

31647 9005 B

AVAILABLE IN
BLACK 31647 9005 B



[View on website](#)



General info

LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.3
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	EPD, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN @ 2700K: LED cluster 18W / CRI>90 (R9: 50) / 2700K-5000K / 2407lm UP @ 2700K: LED cluster 11,2W / CRI>90 (R9: 50) / 2700K-5000K / 1464lm Or DOWN @ 5000K: LED cluster 16,5W / CRI>90 (R9: 50) / 2700K-5000K / 2869lm UP @ 5000K: LED cluster 10,1W / CRI>90 (R9: 50) / 2700K-5000K / 1752lm
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN @ 2700K: 2407lm // 18W // 134lm/W UP @ 2700K: 1464lm // 11,2W // 131lm/W Or DOWN @ 5000K: 2869lm // 16,5W // 174lm/W UP @ 5000K: 1752lm // 10,1W // 173lm/W

Options

WIRELESS CONTROL DIM5

Notes:

DELTALIGHT

OML50 - PRISMATIC LENS DU TW 984mm 950 DIM5

31647 9005 B