



## OML50 - PRISMATIC LENS DU TW 984mm 950 DIM5

31647 9005 B

BESCHIKBAAR IN  
**ZWART** 31647 9005 B



[Bekijk op website](#)



### Algemene info

<b>LOCATIE</b>	binnen
<b>STOF EN WATERDICHTHEID</b>	IP20
<b>GEWICHT (KG)</b>	1.3
<b>INFO</b>	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT

### Elektrische info

<b>ELEKTRISCH</b>	220-240V / 0 50-60Hz
<b>KLASSE</b>	I
<b>VOEDING INBEGREPEN</b>	YES
<b>DIM TYPE</b>	DALI
<b>ENERGIE KLASSE</b>	E
<b>CERTIFICATES</b>	EPD, RCM

### Info lichtbron

<b>LIGHTSOURCE NAME</b>	LED
<b>LICHTBRON</b>	DOWN @ 2700K: LED cluster 18W / CRI>90 (R9: 50) / 2700K-5000K / 2407lm UP @ 2700K: LED cluster 11,2W / CRI>90 (R9: 50) / 2700K-5000K / 1464lm Or DOWN @ 5000K: LED cluster 16,5W / CRI>90 (R9: 50) / 2700K-5000K / 2869lm UP @ 5000K: LED cluster 10,1W / CRI>90 (R9: 50) / 2700K-5000K / 1752lm
<b>SMDC</b>	SDCM3
<b>RISK-GROEP</b>	RG1
<b>LM80</b>	L80 > 60000
<b>LED TECHNIEK (LICHTBRON)</b>	DOWN @ 2700K: 2407lm // 18W // 134lm/W UP @ 2700K: 1464lm // 11,2W // 131lm/W Or DOWN @ 5000K: 2869lm // 16,5W // 174lm/W UP @ 5000K: 1752lm // 10,1W // 173lm/W

### Opties

WIRELESS CONTROL DIM5

Notes:

# DELTALIGHT

## **OML50 - PRISMATIC LENS DU TW 984mm 950 DIM5**

31647 9005 B