

DEEP RINGO DYNAMIC FOCUS TRIMLESS 930

32112 9300 BROB

AVAILABLE IN

BLACK 32112 9300 B

BRUSHED ALU 32112 9300 BRA

BRUSHED ANTHRACITE 32112 9300 BRAT

BRUSHED BROWN BRONZE 32112 9300 BRBB

BRUSHED COPPER 32112 9300 BRCU


BRUSHED GOLD 32112 9300 BRG

BRUSHED OLD BRONZE 32112 9300 BROB

CREAM 32112 9300 CR

PIANO BLACK 32112 9300 PB

WHITE 32112 9300 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - Ø KIT
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	non adjustable

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	G

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	13° (central part only): LED array 5,8W / CRI>90 (R9: 55) / 3000K / 528lm Or 24° central part: LED array 1W / CRI>90 (R9: 55) / 3000K / 63lm 24° ring part: LED cluster 5,5W / CRI>90 (R9: 50) / 3000K / 914lm
RVALUES	13° (central part only): rf: 92 / Rg: 98 24° central part: rf: 92 / Rg: 98 24° ring part: rf: 92 / Rg: 100
SDMC	SDCM2 SDCM3
RISKGROUP	RG2 (threshold 0,6m) RG1
LM80	L90B10 > 41000 L80 > 60000
BEAMANGLE	13°-24°
LED TECHNICS (LIGHT SOURCE)	13° (central part only): 528lm // 5,8W // 94lm/W Or 24° central part: 63lm // 1W // 100lm/W 24° ring part: 914lm // 5,5W // 167lm/W
LED TECHNICS (LUMINAIRE)	13° (central part only): 475lm // 6,7W // 71lm/W Or 24° ring part: 366lm // 6,3W // 58lm/W

DEEP RINGO DYNAMIC FOCUS TRIMLESS 930

32112 9300 BROB

Requirements

MOUNTING KIT R82 TRIMLESS O.F.A.
LED POWER SUPPLY DYNAMIC FOCUS

For detailed installation instructions, please consult the manual : [32112_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY


Ceiling Type	Mounting Kit	
 System ceiling	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Plasterboard	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Stucanet	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Concrete + plaster	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Lintel + plaster	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Hollow-core slab + plaster	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Ventilation in plasterboard	 29810 0100 - MOUNTING KIT SIDE AIR ONLY 1	Required
	 29810 0050 - MOUNTING KIT NO AIR 101	Required
	 29810 0010 - MOUNTING KIT SIDE AIR 101	Required
 Ventilation in concrete + plaster	 29810 0210 - MOUNTING KIT TOP AIR 101	Required
	 29810 0050 - MOUNTING KIT NO AIR 101	Required
	 29810 0200 - MOUNTING KIT TOP AIR ONLY 1	Required
 Cold stretched ceiling	 15212 0070 - MOUNTING KIT R82 TRIMLESS CSC	Required
 Warm stretched ceiling	 15212 0150 - MOUNTING KIT R82 TRIMLESS WSC	Required


DEEP RINGO DYNAMIC FOCUS TRIMLESS 930


32112 9300 BROB

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
 web2print_power_supply_info_box		Min current Max current

	32110 0015	LED POWER SUPPLY DYNAMIC FOCUS DIM5	3	☐
	Dimtype: DALI			
	Cutout dimension (mm): 75			
	32110 0020	LED POWER SUPPLY DYNAMIC FOCUS + WIRELESS CONTROL DIM5	3	☐
	Dimtype: DALI			
	Cutout dimension (mm): 75			

Mounting kits		
	15212 2000	MOUNTING KIT R82 TRIMLESS O.F.A.
	Cutout dimension (mm): 105	
		☐

Mounting kits stretched ceiling		
	15212 0070	MOUNTING KIT R82 TRIMLESS CSC
		☐
	15212 0150	MOUNTING KIT R82 TRIMLESS WSC
		☐

Notes: