


27327 9300 W

Technical drawing of a mechanical part, likely a bracket or support. The drawing shows a cylindrical component with a diameter of $\varnothing 39$ and a length of 92. A rectangular plate with a width of 160 and a height of 7 is attached to the side of the cylinder. The plate has a thickness of 20. A dimension of 11 is indicated for the distance from the center of the cylinder to the inner edge of the plate. A rotation symbol indicates a range of motion from 0° to 35° .



Références optionnelles

1 / 3

TERMINEZ VOTRE SPÉCIFICATION


SMART 48

de luminaires



de luminaires indique combien d'appareils peuvent être raccordés (min -> max) à l'alimentation. Les valeurs avant et après le '|' correspondent respectivement au courant de pilotage minimal et maximal. Les valeurs entre parenthèses s'appliquent au 110V.


Courant min. | Courant max.



300 90 011 SMART 48 MODULATOR DIM9

19

Type de gradation: 1 à 10 V ou DALI ou bouton poussoir



300 90 012 SMART 48 MODULATOR WD

19

Type de gradation: WDL = dimmable sans fil


les alimentations led

de luminaires



de luminaires indique combien d'appareils peuvent être raccordés (min -> max) à l'alimentation. Les valeurs avant et après le '|' correspondent respectivement au courant de pilotage minimal et maximal. Les valeurs entre parenthèses s'appliquent au 110V.


Courant min. | Courant max.



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

10


Type de gradation: non dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

24

Type de gradation: non dimmable




21012 0230 LED POWER SUPPLY 48V-DC / 100W

10

Type de gradation: non dimmable

Dimension de découpe (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W

20

Type de gradation: non dimmable



Dimension de découpe (mm): 40

DELTALIGHT

SPL14 - SPY 39 FOCUS 930 MDL

27327 9300 W

COMPOSABLES COMPATIBLES

SPLITLINE 14 profile		Couleurs disponibles
	27300 0020 SPL14 - PROFILE 2m	
	27300 0030 SPL14 - PROFILE 3m	

Notes: