



CARREE X LED 92733 S1

REFERENCE



202 20 811 922 W

AVAILABLE IN

ALU GREY 202 20 811 922 A

ANTHRACITE 202 20 811 922 N

WHITE 202 20 811 922 W



[View on website](#)



General info

LOCATION	indoor-outdoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	square - 75 x 75
RECESSED DEPTH (MM)	80
THICKNESS OF MOUNTING SURFACE (MM)	max.35
INGRESS PROTECTION	IP44/20
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	0.4
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-33° INCL.PC CLEAR EXCL.LED POWER SUPPLY 350mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	D
CERTIFICATES	CB, EAC, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	33°
LED TECHNICS (LIGHT SOURCE)	753lm // 5,8W // 129lm/W
LED TECHNICS (LUMINAIRE)	599lm // 6,7W // 90lm/W

Requirements

LED POWER SUPPLY 350mA-DC DIM


For detailed installation instructions, please consult the manual : [202_20_811_XXX_HAND.pdf](#)

CEILING COMPATIBILITY


Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Stretched ceiling	-

FINISH YOUR SPECIFICATION

Emergency units











	21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B	☐
	Cutout dimension (mm): 27	
	21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W	☐

LED power supplies

		# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the 'I' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
	300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1	1 ☐
	Dimtype: 1-10V	
	Cutout dimension (mm): 30	
	300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5	1 ☐
	Dimtype: DALI	
	Cutout dimension (mm): 45	

CARREE X LED 92733 SI


202 20 811 922 W

	300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL	1	☐
Dimtype: non-dimmable			
Cutout dimension (mm): 30			
	300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL	1	☐
Dimtype: WDL = wireless dimmable			
Cutout dimension (mm): 45			
	300 90 61 LED POWER SUPPLY MULTI-POWER DIM6	2	☐
Dimtype: mains (phase cut-off) or push button			
Cutout dimension (mm): 56			
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	4(4)	☐
Dimtype: 1-10V or DALI or push button			
Cutout dimension (mm): 82			
	300 90 64 LED POWER SUPPLY MULTI-POWER DIM7	2(1)	☐
Dimtype: 1-10V or push button			
Cutout dimension (mm): 72			
	300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9	2	☐
Dimtype: 1-10V or DALI or push button			
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	2(2)	☐
Dimtype: DALI			
Cutout dimension (mm): 72			
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9	2->6(6)	☐
Dimtype: 1-10V or DALI or push button			
Cutout dimension (mm): 84			
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7	3(2)	☐
Dimtype: 1-10V or push button			
Cutout dimension (mm): 55			
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5	2(2)	☐
Dimtype: DALI			
Cutout dimension (mm): 55			

DELTALIGHT

CARREE X LED 92733 SI

202 20 811 922 W



300 90 135


LED POWER SUPPLY MULTI-POWER HV

3->3



Dimtype: non-dimmable

Cutout dimension (mm): 90



21012 0010


LED POWER SUPPLY MULTI POWER

2



Dimtype: non-dimmable

Cutout dimension (mm): 50



21012 0021


LED POWER SUPPLY MULTI POWER DIM1

3



Dimtype: 1-10V

Cutout dimension (mm): 54



21012 0035


LED POWER SUPPLY MULTI POWER DIM5

3



Dimtype: DALI

Cutout dimension (mm): 54



21012 004W


LED POWER SUPPLY MULTI-POWER WDL

3(3)



Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 84



21012 005W


LED POWER SUPPLY MULTI-POWER COMPACT WDL

3



Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 54



21012 0258


LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8

1



Dimtype: mains (phase cut-off)

Cutout dimension (mm): 50



21012 0298


LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

2



Dimtype: mains (phase cut-off)

Cutout dimension (mm): 48



21012 0480


LED POWER SUPPLY 350mA-DC / 17W IP68

2(2)



Dimtype: non-dimmable

Cutout dimension (mm): 60



21032 0295

LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

2



Dimtype: DALI

Cutout dimension (mm): 30

DELTALIGHT

CARREE X LED 92733 SI

202 20 811 922 W

Notes: