
DELTALIGHT



# DEEP RINGO DYNAMIC FOCUS TRIMLESS 930

**REFERENCE** 32112 9300 W

AVAILABLE IN
**BLACK** 32112 9300 B
**BRUSHED ALU** 32112 9300 BRA
**BRUSHED ANTHRACITE** 32112 9300 BRAT
**BRUSHED BROWN BRONZE** 32112 9300 BRBB
**BRUSHED COPPER** 32112 9300 BRCU
**BRUSHED GOLD** 32112 9300 BRG
**BRUSHED OLD BRONZE** 32112 9300 BROB
**CREAM** 32112 9300 CR
**PIANO BLACK** 32112 9300 PB
**WHITE** 32112 9300 W




View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Ceiling Recessed |
| **CUTOUT SHAPE/SIZE (MM)** | round - Ø KIT |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 0.3 |
| **ADJUSTABILITY** | non adjustable |

| Electrical info | |
|---|---|
| **CLASS** | III |
| **DIM TYPE** | depending on power supply |
| **ENERGY CLASS** | G |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | 13° (central part only): LED array 5,8W / CRI>90 (R9: 55) / 3000K / 528lm<br>Or<br>24° central part: LED array 1W / CRI>90 (R9: 55) / 3000K / 63lm<br>24° ring part: LED cluster 5,5W / CRI>90 (R9: 50) / 3000K / 914lm |
| **SDCM** | SDCM2<br>SDCM3 |
| **RISKGROUP** | RG2 (threshold 0,6m)<br>RG1 |
| **LM80** | L90B10 > 41000<br>L80 > 60000 |
| **BEAMANGLE** | 13°-24° |
| **LED TECHNICS (LIGHT SOURCE)** | 13° (central part only): 528lm // 5,8W // 94lm/W<br>Or<br>24° central part: 63lm // 1W // 100lm/W<br>24° ring part: 914lm // 5,5W // 167lm/W |
| **LED TECHNICS (LUMINAIRE)** | 13° (central part only): 475lm // 6,7W // 71lm/W<br>Or<br>24° ring part: 366lm // 6,3W // 58lm/W |

**Requirements**

MOUNTING KIT R82 TRIMLESS O.F.A.
LED POWER SUPPLY DYNAMIC FOCUS

DELTALIGHT

# DEEP RINGO DYNAMIC FOCUS TRIMLESS 930

32112 9300 W

For detailed installation instructions, please consult the manual : **32112_XXX0_HAND.pdf**

## CEILING COMPATIBILITY

| Ceiling Type | Mounting Kit | |
|---|---|---|
|  **System ceiling** | 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A. | Required |
|  **Plasterboard** | 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A. | Required |
|  **Stucanet** | 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A. | Required |
|  **Concrete + plaster** | 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A. | Required |
|  **Lintel + plaster** | 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A. | Required |
|  **Hollow-core slab + plaster** | 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A. | Required |
|  **Ventilation in plasterboard** | 29810 0100 - MOUNTING KIT SIDE AIR ONLY 1 | Required |
| | 29810 0050 - MOUNTING KIT NO AIR 101 | Required |
| | 29810 0010 - MOUNTING KIT SIDE AIR 101 | Required |
|  **Ventilation in concrete + plaster** | 29810 0210 - MOUNTING KIT TOP AIR 101 | Required |
| | 29810 0050 - MOUNTING KIT NO AIR 101 | Required |
| | 29810 0200 - MOUNTING KIT TOP AIR ONLY 1 | Required |
|  **Cold stretched ceiling** | 15212 0070 - MOUNTING KIT R82 TRIMLESS CSC | Required |
|  **Warm stretched ceiling** | 15212 0150 - MOUNTING KIT R82 TRIMLESS WSC | Required |

## FINISH YOUR SPECIFICATION

### LED power supplies

### # of Fixtures


**Min current | Max current**

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

DELTALIGHT

# DEEP RINGO DYNAMIC FOCUS TRIMLESS 930


32112 9300 W




**32110 0015** LED POWER SUPPLY DYNAMIC FOCUS DIM5 — 3

**Dimtype: DALI**

**Cutout dimension (mm): 75**





**32110 0020** LED POWER SUPPLY DYNAMIC FOCUS + WIRELESS CONTROL DIM5 — 3

**Dimtype: DALI**

**Cutout dimension (mm): 75**


## Mounting kits




**15212 2000** MOUNTING KIT R82 TRIMLESS O.F.A.

**Cutout dimension (mm): 105**

## Mounting kits stretched ceiling




**15212 0070** MOUNTING KIT R82 TRIMLESS CSC




**15212 0150** MOUNTING KIT R82 TRIMLESS WSC

Notes: