



M20/M26H - SPY 391 92740 DIM5

23316 9235 GC

AVAILABLE IN

BLACK 23316 9235 B

BRUSHED ALU 23316 9235 BRA

BRUSHED ANTHRACITE 23316 9235 BRAT

BRUSHED COPPER 23316 9235 BRCU

BRUSHED GOLD 23316 9235 BRG

BRUSHED OLD BRONZE 23316 9235 BROB


FLEMISH BRONZE 23316 9235 FBR

FLEMISH GOLD 23316 9235 FG

GOLD COLOURED 23316 9235 GC

PIANO BLACK 23316 9235 PB

WHITE 23316 9235 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	REFLECTOR WFL-40° EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	844lm // 9,9W // 85lm/W

Remarks

Take a look at our **MAGNETIC PROFILES** movie

Requirements

SPY 39 TUBE or VISOR 39

LED POWER SUPPLY 48V-DC

M20/M26H - SPY 391 92740 DIM5

23316 9235 GC

For detailed installation instructions, please consult the manual : [23316_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION


LED power supplies		# of Fixtures
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
5510090 300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: non-dimmable	10	
63114125 300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN Dimtype: non-dimmable	24	
3017298 21012 0230 LED POWER SUPPLY 48V-DC / 100W Dimtype: non-dimmable Cutout dimension (mm): 40	10	
3022392 21012 0240 LED POWER SUPPLY 48V-DC / 200W Dimtype: non-dimmable Cutout dimension (mm): 40	20	
Light altering devices		
12635 24144 0030 B VISOR 39 B		

DELTALIGHT

M20/M26H - SPY 391 92740 DIM5

23316 9235 GC

Finish your product



24144 0010 B SPY 39 TUBE B

☐

24144 0010 FBR SPY 39 TUBE FBR

☐

24144 0010 FG SPY 39 TUBE FG

☐

24144 0010 GC SPY 39 TUBE GC

☐

24144 0010 W SPY 39 TUBE W

☐

24144 0070 SPY 39 TUBE SBL

☐

COMPATIBLE COMPOSABLES

SHIFTLINE M26H + SBL


Available Colours




30411 9205 SHIFTLINE M26H + SBL 2m DIM5



30411 9305 SHIFTLINE M26H + SBL 2m DIM5



30412 9205 SHIFTLINE M26H + SBL 3m DIM5




30412 9305 SHIFTLINE M26H + SBL 3m DIM5







DELTALIGHT

M20/M26H - SPY 391 92740 DIM5

23316 9235 GC

	30413 9205 SHIFTLINE M26H + SBL 4m DIM5	 
	30413 9305 SHIFTLINE M26H + SBL 4m DIM5	 





SHIFTLINE M26H profile	Available Colours
	23359 0000 SLM26H - PROFILE  
	23359 0010 SLM26H - PROFILE 1m  
	23359 0020 SLM26H - PROFILE 2m          
	23359 0030 SLM26H - PROFILE 3m          

SPLITLINE M20 ST profile	Available Colours
	23397 0000 SPM20 ST - PROFILE  
	23397 0020 SPM20 ST - PROFILE 2m  
	23397 0030 SPM20 ST - PROFILE 3m  

DELTALIGHT

M20/M26H - SPY 391 92740 DIM5

23316 9235 GC

SPLITLINE M20 profile		Available Colours
	420 20 10 00 SPM20 - PROFILE 1m	
	420 20 20 00 SPM20 - PROFILE 2m	
	420 20 30 00 SPM20 - PROFILE 3m	
	23301 0000 SPM20 - PROFILE B	

Notes: