
DELTALIGHT




XY180 S82

REFERENCE 422 121 93 B

AVAILABLE IN
BLACK 422 121 93 B





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.3
ADJUSTABILITY	0° to 120° swiveling, 360° rotatable
INFORMATION	INCL.LED POWER SUPPLY 350mA-DC

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED flex 8,9W / CRI>90 / 3000K / 1050lm)
LED TECHNICS (LIGHT SOURCE)	2100lm // 17,8W // 118lm/W
LED TECHNICS (LUMINAIRE)	1748lm // 20,5W // 85lm/W

Remarks

Look at the XY180 brochure

Options

XY180 CONNECTION BOX
COVERSET R 90-100

For detailed installation instructions, please consult the manual : **422_121_XX_HAND.pdf**


DELTALIGHT

XY180 S82

422 121 93 B

FINISH YOUR SPECIFICATION


Coversets



204 00 90 ANO COVERSET R 90 ANO ☐

204 00 90 B COVERSET R 90 B ☐

204 00 90 W COVERSET R 90 W ☐




204 00 100 ANO COVERSET R 100 ANO ☐

204 00 100 B COVERSET R 100 B ☐

204 00 100 W COVERSET R 100 W ☐

Other



422 99 01 B XY180 CONNECTION BOX B ☐

Notes: